



# SCC2000A

## Crawler Crane 200 Tons Lifting Capacity

Quality Changes the World



- Max. lifting moment:  $144 \times 8 = 1152 \text{t} \cdot \text{m}$
- Max. boom length: 85m
- Max. fixed jib combination: 73m+31m
- Max. luffing jib combination: 58m+58m

The parameters, pictures and standard/optional equipment are only for reference in this brochure, the actual machine is based on the effective price list and contract.



**Crawler Crane Series**  
**SCC2000A**

P03

Main  
Characteristics

- Product Specification
- Safety Device

P09

Technical  
Parameters

- Major Performance & Specifications
- Outline Dimension
- Transport Dimension
- Transport Plan

P19

Cofigurations

- H Configuration
- FJ Configuration
- LJ Configuration




**SCC2000A**  
**SANY CRAWLER CRANE**  
**200 TONS LIFTING CAPACITY**

QUALITY CHANGES THE WORLD

## Main Characteristics

- Page 04 Product Specification
- Page 07 Safety Device



## Product Specification



### Engine

- Model: DCEC (Cummins China) QSL8.9-C325 Diesel engine;
- Type: 4-stroke, water-cooled, vertical in-line 6 cylinders, direct injection, turbo-charger, intercooler, complied with European Non-road Tier III Emission Standard and Chinese Non-road Tier III Emission Standard;
- Displacement: 8.9L;
- Rated power: 242kW/2100rpm;
- Operation power: 234kW/1800rpm;
- Max. Torque: 1385N·m/1500rpm;
- Starter: 24V-6.0kW;
- Radiator: fin type aluminum plate core;
- Air cleaner: Dry type system with main filter element, safety element and resistance indicator;
- Throttle: Grip type hand throttle, electrically-controlled;
- Fuel filter: Replaceable paper element;
- Batteries: Two 12V×180Ah capacity batteries, connected in series;
- Fuel tank capacity: 400L.

### Electrical Control System

- Self-developed SYIC-II integrated control system is adopted with higher integration, precise operation and reliable quality;
- Control system consists of power system, engine system, main control system, LMI system, auxiliary system and safety monitoring system. CAN BUS is used for data communication between controller, monitor and the engine;
- Monitor: the working parameters and status are shown on the monitor, such as the engine speed, fuel volume, engine oil pressure, servo pressure, engine working hours, lifting conditions and boom angle.

### Hydraulic System

- Main pumps: open variable displacement piston pumps of large displacement are adopted to provide oil supply for main actuators of main machine;
- Gear pump: dual gear pump for radiator and control circuit;
- Control: main pump adopts electrically-controlled positive flow control; winch motor adopts limitless adjustable piston motor of variable displacement. The operating components are two cross hydraulic handle, one dual travel pedal control valve to control various actuators proportionally;
- Way of cooling: heat exchanger, fan core and multi-stage cooling;
- Filter: large flow, high precision filter, with bypass valve and transmitter, which can remind the user to replace the filter element in time;
- Max. pressure of system: 32 Mpa;
- Main/aux. load hoist, boom hoist, swing and travel system: 32Mpa;
- Control system: 5 MPa;
- Hydraulic Tank Capacity:460L.

### Main and Auxiliary Load Hoist Mechanism

- Main and aux. hoist winches are driven separately by motor via gearbox. Operating winch handle can control the winch to rotate to two directions, which are lifting and lowering of hook. Excellent inching function is equipped on the machine;
- Drums with fold-line grooves can ensure the wire rope reeved in order in multilayers.

Main Hoisting Mechanism	Drum diameter	630mm
	Rope speed (5th layer)	0-130m/min
	Diameter of wire rope	26mm
	Main load hoist wire rope length	400m
	Rated single line pull	13.5t
Auxiliary Hoisting Mechanism	Drum diameter	630mm
	Rope speed (5th layer)	0-130m/min
	Diameter of wire rope	26mm
	Auxiliary load hoist wire rope length	310m
	Rated single line pull	13.5t



## Product Specification

### Boom Hoist Mechanism

- Boom hoist winch is driven directly by motor via gearbox. Operating winch handle can control the winch to rotate to two directions, which are lifting and lowering of boom;
- Drums with fold-line grooves can ensure the wire rope reeved in order in multilayers.

Boom hoist mechanism	Drum diameter	440mm
	Rope speed (5th layer)	0~46m/min
	Diameter of wire rope	22mm
	Boom hoist wire rope length	250m
Jib hoist mechanism	Drum diameter	500mm
	Rope speed (5th layer)	0~46m/min
	Diameter of wire rope	22mm
	Jib hoist wire rope length	190m

### Swing Mechanism

- Swing brake adopts wet, spring loaded, normally-closed brake, and braking through spring force;
- Swing system, has free slipping function. It is featured in steady starting and control, and excellent inching function. Unique swing buffer design and steadier brake;
- Swing drive: internal engaged swing drive with 360° swing range, and the max. swing speed is 1.3r/min. The max. drive pressure can reach 32MPa;
- Swing ring: three-row roller bearing.

### Cab and Control

- Novel operator's cab with fashionable profile, nice interior and large window glass, which can tilt up by 20° to provide panorama view. There are low and high-beam lights, back-view mirror, heater and A/C, radio and other functions. The layout of seat, handles, control buttons are designed with ergonomic principles to make operation more comfortable;
- Cab layout: Integrated 10.4-inch touch screen, programmable smart switches, and man-machine interaction interface are more perfect;
- Armrest box: on the left and right armrest box are control handles, electrical switches, emergent stop and ignition switch. The armrest box can be adjusted along with the seat;
- Seat: multi-way and multi-level floating adjustable seat with unload switch;
- A/C: cool and heat air; optimized air channels and vents;
- Multiple cameras can present on the monitor at the same time to realize backing video, real-time monitoring of wire rope on each winch, conditions behind the counterweight and surrounding the machine.

### Counterweight

- The stacking mode of counterweight tray and blocks is used for easy assembly, disassembly and transportation;
- Rear counterweight: total weight 74t. Counterweight blocks 6t×10, one counterweight tray 14t;
- Carbody counterweight: total weight 25t, 12.5t×2;
- Rear counterweight self-assembly device is offered as optional.

### Upperworks

- High-strength steel weld framework, with no torsion or deformation. The parts are laid out in the way that is easier for maintenance and service.

## Product Specification



### Lowerworks

- Independent travel driving units are adopted for each side of the crawler, to realize straight walking and turning driven by travel motor through gearbox and drive wheel.

### Crawler Tightening

- The jack is used to push the guide wheel and insert the shim to adjust crawler tension.

### Track Pad

- High strength alloy cast steel track pad ensure long service life;
- The track pads are 1100mm wide, a total of 57 pcs ×2.

### Operating Equipment

- All chords are high-strength steel tubes, and the boom/jib top sheaves are made of high-strength anti-wearing Nylon material protecting wire rope. The hooks are installed with milled welded steel sheave.

### Boom

- Lattice structure. The chord adopts high-strength structural tube and each section is connected through pins;
- Basic boom: 8m boom base + 8m boom top;
- Boom insert: 3m×1, 6m×3, 12m×4;
- Boom length: 16m~85m.

### Fixed Jib

- Lattice structure. The chord adopts high-strength structural tube and each section is connected through pins;
- Basic jib: 5m jib base +3m insert +5m jib top;
- Jib insert: 6m×3;
- Fixed jib: 13m~31m;
- Longest boom + jib: 73m +31m.

### Luffing Jib

- Lattice structure. The chord adopts high-strength structural tube and each section is connected through pins;
- Basic jib: 6.5m jib base +9m insert +6.5m jib top;
- Jib insert: 3m×1,6m×1,9m×3;
- Longest boom + jib: 58m +58m.


### Extension Jib

- The welding structure is connected with main boom through hinge pin, and used for aux. hook operation;
- Length of extension boom: 1.5m.

### Hook Block

- 200t hook, 9 pulleys;
- 150t hook, 7 pulleys;
- 80t hook, 3 pulleys;
- 35t hook, 1 pulley;
- 13.5t ball hook.

### Hook Limitation Height



Hook	L
200t	4.5m
150t	4.2m
80t	4.1m
35t	3.8m

Hook	L'
13.5t	3.3m



## Safety Device

### Assembly/Work Mode Control Switch

- Under the assembly mode, over-hoist limit switch, crane boom limit device and load moment limiter do not work, so as to facilitate the installation of crane;
- All safety limit devices work in the work mode.

### Emergency Stop

- In emergent situation, this button is pressed down to cut off the power supply of whole machine and all actions stop.

### Load Moment Limiter (LMI)

- It is an independent computerized safety control system. LMI can automatically detect the load weight, work radius and boom angle, and present on the display the rated load, actual load, work radius and boom angle. In normal operation, the LML can make a judgment and cut off automatically if the crane moves towards dangerous direction. It can also perform as a black box to record the lifting information;
- It is composed of monitor, angle sensor and force sensor and other parts.

### Over-hoist Limit Switch of Main/Auxiliary Hooks

- Over-hoist protection device comprises of limit switch and weight on boom top, which prevents the hook lifting up too much;
- When the hook lifts up to the limit height, the limit switch activates, buzzer on the left control panel sends alarm, failure indicator light starts to flash, and the hook hoisting action is cut off automatically.

### Over-release Limit Switch of Main/Auxiliary Hooks

- It is comprised of activator in the drum and proximity switch to prevent over release of wire rope. When the rope is paid out close to the last three wraps, the limit switch acts, and the system sends alarm through buzzer and show the alarm on the instrument panel, automatically cutting off the winch action.

### Function Lock Lever

- If the function lock lever is not in work position, all the other handles won't work, which prevents any mis-operation caused by accidental collision.

### Boom Hoist Drum Lock

- Pawl lock is used on boom hoist winch, which needs to unlock by switch before operation, in order to prevent mis-operation of handles and ensure safety during nonwork time.

### Swing Lock Device

- Swing Lock can lock the machine at four positions, front and back, left and right.

### Boom Limit Device

- When the boom elevation angle reaches the max. set limit, the buzzer sounds and boom action cut off. This protection is two-stage control ensured by both LML system and travel switch.

### Back-stop Device

- Its major components are nesting tubes and spring, in order to buffer the boom backlash and prevent further tipping back.

### Boom Angle Indicator

- Pendulum angle indicator is fixed on the side of boom base close to the cab, so as to provide convenience to the operator.

### Hook Latch

- The hook is provided with a baffle to prevent wire rope from falling off.

## Safety Device



### Lightning Protection Device

- It is offered as an optional feature, which includes the grounding device that can effectively protect the electric system elements and workers from lightning.

### Tri-color Load Indicator

- The load indication light has three colors, green, yellow and red, and the real time load status is presented on the display. When the actual load is smaller than 90% of rated load, the green light is on;
- When the actual load is larger than 90% and smaller than 100%, the yellow light is on, the alarm light flashes and sends out intermittent sirens;
- When the actual load reaches 100% of rated load, the red light is on, the alarm light flashes and sends out continuous sirens;
- When the actual load reaches 102% of rated load, the system will automatically cut off the crane operation in dangerous trend.

### Audio-visual Alarm

- When the engine is working, the light flashes; when the machine is traveling or swinging, it sends out sirens.

### Swing Indicator Light

- The swing indicator light flashes during traveling or swing.

### Illuminating Light

- The machine is equipped with the low beam light and high beam light at the front of the cab, illumination light at cab, and other night lights, boom lights to improve the visibility during construction.

### Camera

- SSet on the handrail at the front of right sheet metal, so as to monitor the rear part of machine.

### Pharos

- Pharos is mounted on the top of boom/jib to indicate the height.

### Anemometer

- It is mounted on the top of boom/jib, and displayed on the monitor in the cab.

### Electronic Level Indicator

- It displays the tipping angle of crane on the monitor in real time, protecting the machine from dangerous situation.

### Seat Interlock


- Put down the function lock lever on the left side of cab seat or if the operator leaves the seat, all control levers will be deactivated to prevent any mis-operation due to accidental collision.

### Engine Power Limit Load Adjustment and Stalling Protection

- The controller monitors the engine power to prevent engine getting stuck and stalling.

### Engine Status Monitoring

- The engine status will be presented, such as engine coolant temperature, fuel volume, total work hours, engine oil pressure, engine speed, battery charging, voltage.




**SCC2000A**  
**SANY CRAWLER CRANE**  
**200 TONS LIFTING CAPACITY**

QUALITY CHANGES THE WORLD

## Technical Parameters

- Page 10 Major Performance Specifications
- Page 11 Outline Dimension
- Page 12 Transport Dimension
- Page 17 Transportation Plan




## Major Performance Specifications


Major Performance & Specifications of SCC2000A			
Performance Indicators		Unit	Parameter
Boom configuration	Maximum rated lifting capacity	t	200
	Maximum rated lifting moment	t·m	1152(=144×8)
	Boom length	m	16~85
Fixed jib configuration	Maximum rated lifting capacity	t	36
	Jib length	m	13-31
	Longest main boom + jib	m	73+31
Luffing jib configuration	Maximum rated lifting capacity	t	63
	Jib length	m	22~58
	Longest main boom + luffing jib	m	58+58
Operation speed	Rope speed of main/aux. load hoist (5th layer)	m/min	0~130
	Boom hoist winch rope speed (5th layer)	m/min	0~46
	Slewing speed	rpm	0~1.3
	Travelling speed	km/h	0~1
Engine	Output power	kW	242
	Rated speed	rpm	2100
Transport parameter	Max. transport weight of basic machine (with boom base)	t	45
	Maximum transport dimension of basic machine (L x W x H, mm)	mm	17500×3000×3230
Other parameters	Average ground bearing pressure	MPa	0.118
	Grade ability	%	30

Unit: mm

### Outline Dimension




## Transportation Dimensions




**Basic Machine (Mode 1: with boom base, rear counterweight self-assembly device, no reeving winch or jib luffing winch)** ×1

Length(L)	17.5m
Width(W)	3.00m
Height(H)	3.23m
Weight	45t




**Basic Machine (Mode 2: with A-frame, rear counterweight self-assembly device, boom base, reeving winch and jib luffing winch)** ×1

Length(L)	17.5m
Width(W)	3.00m
Height(H)	3.23m
Weight	46.98t




**Basic Machine (Mode 3: with A-frame, rear counterweight self-assembly device, no boom base)** ×1

Length(L)	11.3m
Width(W)	3.00m
Height(H)	3.23m
Weight	41.3t



**Crawler Assembly** ×2


Length(L)	8.90m
Width(W)	1.46m
Height(H)	1.34m
Weight	20.3t



**Boom base (with jib luffing winch)** ×1

Length(L)	8.78m
Width(W)	2.36m
Height(H)	2.91m
Weight	5.68t


Note: the weight of jib luffing winch is 1.43t



**Boom Top** ×1


Length(L)	8.78m
Width(W)	2.23m
Height(H)	2.92m
Weight	3.32t

## Transportation Dimensions




### 3m Boom insert × 1

Length(L)	3.18m
Width(W)	2.23m
Height(H)	2.38m
Weight	0.82t




### 6m Boom insert × 3

Length(L)	6.18m
Width(W)	2.23m
Height(H)	2.38m
Weight	1.31t




### 12m Boom insert × 4

Length(L)	12.18m
Width(W)	2.23m
Height(H)	2.38m
Weight	2.43t



### Extension jib × 1


Length(L)	1.96m
Width(W)	0.76m
Height(H)	1.03m
Weight	0.24t



### Fixed jib base (with strut and tapered pendant strap) × 1

Length(L)	5.19m
Width(W)	2.16m
Height(H)	1.66m
Weight	1.17t


Note: the weight of the strut is 0.45t,  
and the tapered pendant strap is 0.15t



### Fixed jib top × 1

Length(L)	5.41m
Width(W)	1.17m
Height(H)	1.06m
Weight	0.59t


## Transport Dimensions



### 3m fixed jib insert

×1


Length(L)	3.12m
Width(W)	1.17m
Height(H)	1.06m
Weight	0.22t



### 6m fixed jib insert

×3


Length(L)	6.12m
Width(W)	1.17m
Height(H)	1.06m
Weight	0.4t



### Luffing jib base (with mast)

×1


Length(L)	8.55m
Width(W)	2.19m
Height(H)	3.16m
Weight	4.5t



### Luffing jib top (with extension jib)

×1


Length(L)	7.75m
Width(W)	1.61m
Height(H)	1.85m
Weight	1.5t



### 3m luffing jib insert

×1

Length(L)	3.14m
Width(W)	1.61m
Height(H)	1.54m
Weight	0.48t




### 6m luffing jib insert

×1


Length(L)	6.14m
Width(W)	1.61m
Height(H)	1.54m
Weight	0.79t

## Transportation Dimensions




### 9m luffing jib insert × 4

Length(L)	9.14m
Width(W)	1.61m
Height(H)	1.54m
Weight	1.08t




### Carbody Counterweight × 2

Length(L)	4.55m
Width(W)	1.35m
Height(H)	0.73m
Weight	12.5t




### Counterweight tray × 1

Length(L)	6.52m
Width(W)	2.33m
Height(H)	0.52m
Weight	14t




### Counterweight block 10

Length(L)	2.29m
Width(W)	2.33m
Height(H)	0.57m
Weight	6t



### 200t Hook × 1


Length(L)	2.44m
Width(W)	0.91m
Height(H)	1.2m
Weight	3.67t



### 150t Hook × 1

Length(L)	2.45m
Width(W)	0.91m
Height(H)	0.95m
Weight	2.91t


## Transport Dimensions



### 80t Hook

×1


Length(L)	2.13m
Width(W)	0.82m
Height(H)	0.62m
Weight	1.64t



### 35t Hook

×1

Length(L)	1.88m
Width(W)	0.82m
Height(H)	0.46m
Weight	1.11t



### 13.5t Ball hook

×1

Length(L)	0.95m
Width(W)	0.43m
Height(H)	0.43m
Weight	0.45t


#### Remarks:

- 1.The transport dimensions for the parts are for reference that do not draw to the scale. The dimensions listed above are design values excluding packing.
- 2.Weight is design values. It maybe different due to manufacturing tolerances.


## Transport Plan

### Transport with crawler frame


Trailer 1	<ul style="list-style-type: none"> <li>50t low deck trailer, 13.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>Basic Machine (with four winches, carbody assembly, A-frame, wire rope) 41.27t</li> <li>Boom base (include jib hoist winch and jib hoist wire rope) 5.68t</li> <li>Boom base outer pendant strap 0.03t</li> </ul>
Weight	<ul style="list-style-type: none"> <li>46.98t</li> </ul>




Trailer 2	<ul style="list-style-type: none"> <li>35t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>12m boom insert, 2.43t</li> <li>6m boom insert, 1.31t</li> <li>Rear counterweight tray, 14t</li> <li>Rear counterweight block x2, 12t</li> <li>9m luffing jib insert, 1.08t</li> <li>Fixed jib base with strut only, 1.05t</li> <li>Tapered pendant strap, 0.15t</li> <li>Fixed jib top, 0.59t</li> <li>3m fixed jib insert, 0.22t</li> <li>6m boom outer pendant strap, 0.19t</li> </ul>
Weight	<ul style="list-style-type: none"> <li>33.02t</li> </ul>



Trailer 3	<ul style="list-style-type: none"> <li>35t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>12m boom insert, 2.43t</li> <li>6m boom insert, 1.31t</li> <li>Rear counterweight block x4, 24t</li> <li>13.5t ball hook, 0.45t</li> <li>9m luffing jib insert, 1.08t</li> <li>3m luffing jib insert, 0.48t</li> <li>6m fixed jib insert, 0.4t</li> <li>12m boom outer pendant strap, 0.34t</li> </ul>
Weight	<ul style="list-style-type: none"> <li>30.49t</li> </ul>




Trailer 4	<ul style="list-style-type: none"> <li>35t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>12m boom insert, 2.43t</li> <li>6m boom insert, 1.31t</li> <li>9m luffing jib insert, 1.08t</li> <li>6m fixed jib insert, 0.4t</li> <li>Rear counterweight x4, 24t</li> <li>80t hook block, 1.64t</li> <li>35t hook block, 1.11t</li> <li>12m boom outer pendant strap, 0.34t</li> </ul>
Weight	<ul style="list-style-type: none"> <li>32.31t</li> </ul>




## Transport Plan


Trailer 5	<ul style="list-style-type: none"> <li>30t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>Boom base, 3.32t</li> <li>Extension jib, 0.24t</li> <li>Luffing jib base with strut, 4.5t</li> <li>200t hook block, 3.67t</li> <li>150t hook block, 2.91t</li> <li>Boom top outer pendant strap, 0.24t</li> <li>Packing case, 1t</li> </ul>
Weight	15.9t




Trailer 6	<ul style="list-style-type: none"> <li>45t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>Left and right track frame (stagger the position), 40.6t</li> <li>3m boom insert, 0.82t</li> <li>3m boom outer pendant strap, 0.11t</li> <li>9m luffing jib insert, 1.08t</li> <li>6m fixed jib insert, 0.4t</li> </ul>
Weight	43.01t



Trailer 7	<ul style="list-style-type: none"> <li>30t trailer, 17.5m long, 3m wide</li> </ul>
Part(s)	<ul style="list-style-type: none"> <li>12m boom insert, 2.43t</li> <li>Luffing jib top with extension jib, 1.5t</li> <li>6m luffing jib insert, 0.79t</li> <li>Carbody counterweight x2, 25t</li> <li>12m boom outer pendant strap, 0.34t</li> </ul>
Weight	30.06t





**SCC2000A**  
**SANY CRAWLER CRANE**  
**200 TONS LIFTING CAPACITY**


QUALITY CHANGES THE WORLD

## Cofigurations

- Page 21 H Configuration
- Page 25 FJ Configuration
- Page 35 LJ Configuration

> 19

**Boom Combination**




H configuration

FJ configuration


LJ configuration

## H Configuration




Note: ★ means recommended boom combination for purchasing.

	8m	Boom base
	8m	Boom top
	3m	Boom insert
	6m	Boom insert
	12m	Boom insert



H configuration: 16m-85m

# H Working Radius



Unit: t

## H Load Chart

Note:

- 1.The rated load in the load chart is calculated complying with EN 13000;
- 2.The working radius is the horizontal distance from the load center to the swing center;
- 3.The actual lifting capacity must subtract the weight of hooks and other riggings from the rated capacity in the load chart.
- 4.The load value is calculated when the object is hung freely,without considering the influence of wind on the load, ground conditions and slope, operation speed and the influence of any other negative factors over safe operation. Therefore, the operator bears the responsibility of making a judgement and decreasing the load and lowering speed.
- 5.All ratings are calculated when the machine is parking on firm and level ground with less than 1% gradient.

Load chart –H(Main hook, Boom 16~85m, Without extension jib) 1/2


Boom length/ radius (m)	16	19	22	25	28	31	34	37	40	43	46	49	Boom length/ radius (m)
5	200.0												5
6	184.0	183.0	169.8										6
7	162.8	163.8	161.1	152.2	142.1								7
8	144.0	142.5	141.9	140.1	135.8	130.7	118.8	113.9					8
9	126.2	125.7	125.2	122.5	120.0	116.2	113.1	110.4	102.2	96.5			9
10	106.5	106.0	105.3	104.6	104.1	103.9	101.5	99.2	97.0	93.4	87.7	83.4	10
12	83.9	83.8	83.7	83.6	83.5	83.4	83.3	81.6	79.9	78.2	76.7	75.2	12
14	67.8	67.7	67.6	67.5	67.4	67.2	67.2	67.0	66.9	66.5	65.2	63.9	14
16	56.7	56.6	56.5	56.4	56.3	56.1	56.0	55.9	55.7	55.6	55.5	55.3	16
18		48.5	48.4	48.2	48.1	47.9	47.9	47.7	47.6	47.4	47.3	47.1	18
20			42.2	42.0	41.9	41.7	41.7	41.5	41.3	41.1	41.0	40.9	20
22				37.2	37.0	36.8	36.8	36.6	36.4	36.2	36.1	35.9	22
24					33.1	32.9	32.8	32.6	32.5	32.3	32.2	32.0	24
26					29.8	29.6	29.6	29.4	29.2	29.0	28.9	28.7	26
28						26.9	26.8	26.6	26.5	26.2	26.1	25.9	28
30							24.5	24.3	24.1	23.9	23.8	23.6	30
32								22.3	22.1	21.9	21.8	21.6	32
34								20.5	20.4	20.1	20.0	19.8	34
36									18.8	18.6	18.5	18.3	36
38										17.2	17.1	16.9	38
40											15.9	15.7	40
42												14.6	42
44												13.6	44
46													46
48													48
50													50
52													52
54													54
56													56
58													58
60													60
62													62
64													64
66													66
68													68
70													70
72													72
74													74
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	16	14	13	12	11	10	9	9	8	8	7	7	Parts of line

**H Load Chart**


Load chart -H(Main hook, Boom 16~85m, Without extension jib) 2/2

Boom length/ radius (m)	52	55	58	61	64	67	70	73	76	79	82	85	Boom length/ radius (m)
5													5
6													6
7													7
8													8
9													9
10	77.2												10
12	73.9	71.3	67.2	61.6	56.1								12
14	62.7	61.5	60.5	59.5	54.4	51.0	46.1	42.6	39.1				14
16	54.5	53.4	52.5	51.5	50.6	49.8	45.3	42.1	38.6	35.1	31.9	28.9	16
18	46.9	46.8	46.3	45.4	44.6	43.7	43.0	41.5	37.5	34.0	30.9	27.9	18
20	40.7	40.5	40.4	40.2	39.8	39.0	38.3	37.6	36.5	33.0	29.8	26.9	20
22	35.8	35.6	35.4	35.2	35.1	34.9	34.5	33.8	33.1	31.9	28.9	26.0	22
24	31.8	31.6	31.5	31.3	31.1	30.9	30.7	30.5	30.0	29.3	27.9	25.1	24
26	28.5	28.3	28.2	28.0	27.8	27.6	27.4	27.2	27.0	26.7	26.1	24.2	26
28	25.8	25.5	25.4	25.2	25.0	24.8	24.7	24.4	24.3	24.0	23.8	23.3	28
30	23.4	23.2	23.1	22.8	22.7	22.4	22.3	22.1	21.9	21.7	21.5	21.2	30
32	21.4	21.2	21.0	20.8	20.6	20.4	20.3	20.0	19.9	19.6	19.4	19.2	32
34	19.6	19.4	19.3	19.0	18.9	18.6	18.5	18.3	18.1	17.9	17.7	17.4	34
36	18.1	17.9	17.7	17.5	17.3	17.1	16.9	16.7	16.5	16.3	16.1	15.9	36
38	16.7	16.5	16.4	16.1	15.9	15.7	15.6	15.3	15.1	14.9	14.7	14.5	38
40	15.5	15.3	15.1	14.9	14.7	14.5	14.3	14.1	13.9	13.7	13.5	13.3	40
42	14.4	14.2	14.0	13.8	13.6	13.4	13.2	13.0	12.8	12.6	12.4	12.1	42
44	13.4	13.2	13.0	12.8	12.6	12.4	12.2	12.0	11.8	11.6	11.4	11.1	44
46	12.5	12.3	12.1	11.9	11.7	11.5	11.3	11.1	10.9	10.7	10.5	10.2	46
48		11.4	11.3	11.1	10.9	10.7	10.5	10.3	10.1	9.8	9.6	9.4	48
50			10.6	10.3	10.1	9.9	9.8	9.5	9.3	9.1	8.9	8.7	50
52			9.9	9.6	9.4	9.2	9.1	8.8	8.6	8.4	8.2	8.0	52
54				9.0	8.8	8.6	8.4	8.2	8.0	7.8	7.6	7.3	54
56					8.2	8.0	7.8	7.6	7.4	7.2	7.0	6.7	56
58						7.4	7.3	7.0	6.8	6.6	6.4	6.2	58
60						6.9	6.8	6.5	6.3	6.1	5.9	5.6	60
62							6.3	6.1	5.9	5.6	5.4	5.1	62
64								5.6	5.4	5.2	5.0	4.6	64
66									5.0	4.8	4.5	4.2	66
68										4.4	4.1	3.7	68
70										4.0	3.7	3.3	70
72											3.3	3.0	72
74												2.6	74
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	6	6	6	5	5	4	4	4	3	3	3	3	Parts of line

## FJ Configuration




	5m	Jib base
	5m	Jib top
	6m	Jib insert
	3m	Jib insert



FJ configuration  
(28m~73m)+(13m~31m)

## FJ Working Radius



Unit: t

## FJ Load Chart

**Note:**

- 1.The rated load in the load chart is calculated complying with EN 13000;
- 2.The working radius is the horizontal distance from the load center to the swing center;
- 3.The actual lifting capacity must subtract the weight of hooks and other riggings from the rated capacity in the load chart.
- 4.The load value is calculated when the object is hung freely,without considering the influence of wind on the load, ground conditions and slope, operation speed and the influence of any other negative factors over safe operation. Therefore, the operator bears the responsibility of making a judgement and decreasing the load and lowering speed.
- 5.All ratings are calculated when the machine is parking on firm and level ground with less than 1% gradient.

### Load chart –FJa( Aux. hook, boom 28~73m) 1/8

Jib 13m, Boom to jib angle 10°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
12	36.0	35.5															12
14	35.1	34.7	34.3	34.0	33.7	33.4											14
16	33.8	33.5	33.2	32.9	32.6	32.3	32.0	31.7	31.3	31.0							16
18	32.5	32.2	31.9	31.6	31.3	31.0	30.6	30.3	30.0	29.6	29.2	28.8	28.3	27.7			18
20	31.3	31.0	30.7	30.4	30.1	29.7	29.3	29.0	28.6	28.2	27.7	27.2	26.6	26.1	25.6	25.1	20
22	30.0	29.7	29.4	29.1	28.8	28.4	28.0	27.6	27.2	26.8	26.4	25.8	25.2	24.7	24.1	23.5	22
24	28.7	28.4	28.1	27.7	27.3	26.9	26.5	26.1	25.8	25.5	25.0	24.4	23.8	23.2	22.6	22.0	24
26	27.1	26.8	26.5	26.2	25.8	25.5	25.1	24.8	24.5	24.1	23.3	22.8	22.2	21.7	21.1	20.5	26
28	25.4	25.2	24.9	24.6	24.3	23.9	23.5	23.2	22.9	22.3	21.8	21.3	20.7	20.2	19.6	19.1	28
30	24.0	23.7	23.4	23.1	22.7	22.3	22.0	21.7	21.3	20.6	20.3	20.0	19.5	19.0	18.3	17.7	30
32	22.7	22.4	22.1	21.8	21.4	21.1	20.8	20.5	20.2	19.2	18.9	18.6	18.2	17.7	17.2	16.6	32
34	21.3	21.0	20.7	20.4	20.1	19.8	19.5	19.2	18.9	18.2	17.8	17.3	16.9	16.4	15.9	15.5	34
36	20.0	19.7	19.5	19.3	19.1	18.8	18.4	18.1	17.8	17.3	17.0	16.2	15.7	15.2	14.8	14.4	36
38	18.6	18.4	18.2	18.0	17.8	17.6	17.3	17.0	16.6	16.2	15.8	15.5	14.8	14.3	13.8	13.4	38
40		17.1	17.0	16.8	16.6	16.4	16.2	16.0	15.8	15.5	15.2	14.7	14.1	13.7	13.1	12.5	40
42			15.9	15.7	15.5	15.3	15.1	14.9	14.7	14.5	14.3	14.0	13.5	13.1	12.5	12.0	42
44				14.7	14.5	14.3	14.1	13.9	13.7	13.5	13.3	13.1	12.9	12.5	11.9	11.4	44
46				13.8	13.6	13.4	13.2	13.0	12.8	12.6	12.4	12.2	12.0	11.8	11.4	10.9	46
48					12.8	12.5	12.4	12.2	12.0	11.8	11.6	11.4	11.2	11.0	10.7	10.3	48
50						11.8	11.6	11.4	11.2	11.0	10.9	10.6	10.4	10.2	10.0	9.8	50
52							11.0	10.7	10.5	10.3	10.2	9.9	9.7	9.5	9.3	9.1	52
54							10.3	10.1	9.9	9.7	9.5	9.3	9.1	8.8	8.6	8.4	54
56								9.5	9.3	9.1	8.9	8.7	8.4	8.2	8.0	7.7	56
58									8.7	8.5	8.3	8.1	7.9	7.6	7.4	7.1	58
60										8.0	7.8	7.5	7.3	7.0	6.9	6.6	60
62											7.5	7.3	7.0	6.8	6.5	6.3	62
64												6.8	6.5	6.3	6.0	5.9	64
66													6.1	5.9	5.6	5.4	66
68														5.4	5.2	5.0	68
70															4.8	4.6	70
72																4.4	72
74																	74
76																	76
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	3	3	3	3	3	3	3	3	3	3	3	3	3	3	2	2	Parts of line

## FJ Load Chart

Load chart -FJa( Aux. hook, boom 28~73m) 2/8																	
Jib 19m, Boom to jib angle 10°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
14	28.0	27.9															14
16	26.8	26.9	27.0	27.1	27.0	26.9											16
18	25.7	25.8	25.9	26.0	26.1	26.2	26.3	26.2	25.9	25.8							18
20	24.5	24.6	24.8	24.9	25.0	25.1	25.2	25.3	25.4	25.3	25.2	24.8	24.6	24.2			20
22	23.1	23.2	23.4	23.5	23.6	23.7	23.8	23.9	24.0	24.1	24.2	24.3	24.1	23.9	23.6	22.7	22
24	21.8	21.9	22.1	22.2	22.3	22.4	22.5	22.6	22.7	22.8	22.9	23.0	23.1	23.2	22.9	22.3	24
26	20.2	20.3	20.6	20.7	20.8	20.9	21.0	21.1	21.2	21.3	21.4	21.5	21.6	21.7	21.8	21.6	26
28	18.7	18.8	19.1	19.2	19.3	19.4	19.5	19.6	19.7	19.8	19.9	20.0	20.1	20.2	20.2	19.8	28
30	17.3	17.4	17.8	17.9	18.0	18.1	18.2	18.3	18.4	18.5	18.6	18.7	18.8	18.9	18.6	18.2	30
32	16.4	16.5	16.7	16.8	16.9	17.0	17.1	17.2	17.3	17.4	17.5	17.6	17.7	17.6	17.2	16.7	32
34	15.6	15.7	15.9	16.0	16.1	16.2	16.3	16.4	16.5	16.6	16.7	16.8	16.7	16.3	15.9	15.5	34
36	14.9	15.0	15.2	15.3	15.4	15.5	15.6	15.7	15.8	15.9	16.0	16.0	15.6	15.2	14.8	14.4	36
38	14.1	14.2	14.4	14.5	14.6	14.7	14.8	14.9	15.0	15.1	15.2	15.0	14.6	14.1	13.8	13.4	38
40	13.6	13.7	13.8	13.9	14.0	14.1	14.2	14.3	14.4	14.5	14.6	14.7	13.6	13.2	12.9	12.4	40
42	12.9	13.0	13.1	13.2	13.3	13.4	13.5	13.6	13.7	13.8	13.9	14.0	12.8	12.4	12.0	11.6	42
44	12.2	12.3	12.5	12.6	12.7	12.8	12.9	13.0	13.1	13.2	13.3	13.4	12.2	11.6	11.2	10.8	44
46		11.8	12.0	12.1	12.2	12.3	12.4	12.5	12.6	12.7	12.7	12.5	11.6	11.0	10.6	10.2	46
48			11.5	11.6	11.7	11.8	11.9	12.0	12.1	12.0	11.9	11.7	11.0	10.5	10.0	9.5	48
50				11.1	11.2	11.3	11.4	11.5	11.5	11.3	11.1	10.9	10.5	10.1	9.7	9.2	50
52				10.6	10.7	10.8	10.9	11.0	10.8	10.6	10.4	10.2	10.0	9.7	9.3	8.8	52
54					10.2	10.3	10.4	10.3	10.1	9.9	9.8	9.6	9.4	9.1	8.8	8.5	54
56						9.8	9.9	9.7	9.6	9.3	9.2	9.0	8.8	8.5	8.2	7.9	56
58							9.4	9.2	9.0	8.8	8.6	8.4	8.2	7.9	7.7	7.5	58
60								8.7	8.5	8.3	8.1	7.8	7.6	7.4	7.2	6.9	60
62								8.2	8.0	7.8	7.6	7.3	7.1	6.8	6.7	6.4	62
64									7.5	7.3	7.1	6.8	6.6	6.4	6.2	5.9	64
66										6.8	6.7	6.4	6.2	5.9	5.7	5.5	66
68											6.2	6.0	5.7	5.5	5.3	5.0	68
70											5.8	5.6	5.3	5.1	4.9	4.6	70
72												5.2	5.0	4.7	4.5	4.2	72
74													4.6	4.3	4.1	3.9	74
76														4.0	3.8	3.5	76
78														3.7	3.5	3.2	78
80															3.2	2.9	80
Counter weight(t) Parts of line	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t) Parts of line
	3	3	2	3	2	2	2	2	2	2	2	2	2	2	2	2	

Unit: t

## FJ Load Chart

### Load chart -FJa( Aux. hook, boom 28~73m) 3/8

Jib 25m, Boom to jib angle 10°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
16	20.6	20.7															16
18	19.8	20.0	20.1	20.2	20.2	20.3											18
20	19.1	19.2	19.4	19.5	19.6	19.7	19.7	19.7	19.6	19.6							20
22	18.4	18.5	18.6	18.7	18.8	19.0	19.2	19.2	19.2	19.2	19.1	18.8	18.4	17.9			22
24	17.6	17.7	17.8	17.9	18.0	18.3	18.6	18.6	18.7	18.7	18.7	18.4	18.0	17.6	17.1	16.5	24
26	16.8	16.9	17.0	17.1	17.2	17.3	17.6	17.9	18.3	18.3	18.2	18.0	17.7	17.3	16.8	16.2	26
28	15.9	16.0	16.1	16.2	16.3	16.4	16.5	17.2	17.7	17.8	17.8	17.7	17.4	17.0	16.5	16.0	28
30	14.8	14.9	15.0	15.1	15.2	15.3	15.4	16.4	17.1	17.4	17.3	17.3	17.1	16.7	16.2	15.7	30
32	13.7	13.8	13.9	14.0	14.1	14.2	14.3	15.5	16.4	16.8	16.9	16.8	16.7	16.4	16.0	15.4	32
34	12.8	12.9	13.0	13.1	13.2	13.3	13.4	14.5	15.4	16.2	16.3	16.2	16.1	15.9	15.5	15.0	34
36	12.1	12.2	12.3	12.4	12.5	12.6	12.7	13.7	14.6	15.7	15.8	15.6	15.5	15.1	14.7	14.3	36
38	11.5	11.6	11.7	11.8	11.9	12.0	12.1	13.1	14.1	15.0	15.0	14.8	14.5	14.0	13.7	13.3	38
40	10.9	11.0	11.1	11.2	11.3	11.4	11.5	12.5	13.5	14.5	14.3	13.9	13.5	13.1	12.8	12.4	40
42	10.4	10.5	10.6	10.7	10.8	10.9	11.0	12.1	13.1	14.1	13.7	13.0	12.7	12.3	12.0	11.6	42
44	10.0	10.1	10.2	10.3	10.4	10.5	10.6	11.7	12.7	13.5	13.1	12.5	12.0	11.5	11.2	10.8	44
46	9.6	9.7	9.8	9.9	10.0	10.1	10.2	11.3	12.3	12.8	12.5	12.0	11.4	11.1	10.5	10.1	46
48	9.2	9.3	9.4	9.5	9.6	9.7	9.8	10.9	11.9	12.1	12.0	11.6	11.1	10.8	10.1	9.5	48
50		9.0	9.1	9.2	9.3	9.4	9.5	10.5	11.5	11.5	11.3	11.0	10.7	10.4	9.8	9.1	50
52		8.8	8.9	9.0	9.1	9.2	9.3	10.2	11.0	10.8	10.6	10.4	10.2	10.0	9.5	8.8	52
54			8.7	8.8	8.9	9.0	9.1	10.0	10.4	10.1	10.0	9.8	9.6	9.4	9.1	8.5	54
56				8.6	8.7	8.8	8.9	9.6	9.8	9.5	9.4	9.2	9.0	8.8	8.6	8.2	56
58					8.5	8.6	8.7	9.3	9.2	9.0	8.8	8.6	8.4	8.2	8.0	7.8	58
60					8.3	8.4	8.5	8.9	8.7	8.5	8.3	8.1	7.9	7.6	7.4	7.2	60
62						8.2	8.3	8.4	8.2	8.0	7.8	7.6	7.4	7.1	6.9	6.7	62
64							8.1	7.9	7.7	7.5	7.3	7.1	6.9	6.6	6.4	6.2	64
66								7.5	7.3	7.1	6.9	6.6	6.4	6.2	6.0	5.7	66
68								7.1	6.9	6.6	6.5	6.2	6.0	5.7	5.5	5.3	68
70									6.5	6.2	6.1	5.8	5.6	5.3	5.1	4.9	70
72										5.9	5.7	5.4	5.2	4.9	4.8	4.5	72
74											5.3	5.1	4.8	4.6	4.4	4.1	74
76												4.7	4.5	4.2	4.1	3.8	76
78												4.4	4.2	3.9	3.7	3.5	78
80													3.9	3.6	3.4	3.2	80
82														3.3	3.1	2.9	82
84															2.8	2.6	84
86															2.5	2.3	86
88																2.1	88
Counter weight(t) Parts of line	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t) Parts of line
	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	

## FJ Load Chart

Load chart -FJa( Aux. hook, boom 28~73m) 4/8																	
Jib 31m, Boom to jib angle 10°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
18	13.5	13.5															18
20	13.0	13.0	13.1	13.1	13.1	13.1											20
22	12.5	12.6	12.7	12.7	12.7	12.7	12.8	12.7	12.7	12.6							22
24	12.1	12.2	12.3	12.3	12.3	12.4	12.4	12.4	12.4	12.3	12.3	12.2	12.1	11.9			24
26	11.7	11.8	11.9	11.9	12.0	12.0	12.1	12.1	12.1	12.0	12.0	11.9	11.8	11.7	11.5	11.3	26
28	11.3	11.4	11.5	11.6	11.7	11.7	11.7	11.8	11.8	11.7	11.7	11.7	11.6	11.5	11.3	11.1	28
30	10.7	11.1	11.2	11.2	11.3	11.4	11.4	11.4	11.5	11.5	11.5	11.4	11.3	11.2	11.1	10.9	30
32	10.0	10.4	10.8	10.9	11.0	11.1	11.1	11.2	11.2	11.2	11.2	11.1	11.1	11.0	10.9	10.7	32
34	9.5	9.8	10.2	10.6	10.7	10.8	10.8	10.9	10.9	10.9	10.9	10.9	10.9	10.8	10.7	10.5	34
36	9.0	9.3	9.7	10.1	10.3	10.5	10.6	10.6	10.7	10.7	10.7	10.7	10.6	10.6	10.5	10.3	36
38	8.5	8.8	9.2	9.5	9.8	10.1	10.3	10.3	10.4	10.4	10.5	10.4	10.4	10.4	10.3	10.1	38
40	8.1	8.4	8.7	9.1	9.4	9.7	10.0	10.1	10.2	10.2	10.2	10.2	10.2	10.1	10.1	9.9	40
42	7.7	8.1	8.3	8.7	9.0	9.3	9.6	9.9	9.9	10.0	10.0	10.0	10.0	9.9	9.9	9.8	42
44	7.3	7.6	8.0	8.3	8.6	8.9	9.2	9.5	9.7	9.7	9.8	9.8	9.8	9.8	9.7	9.6	44
46	7.0	7.3	7.6	7.9	8.2	8.5	8.8	9.2	9.5	9.5	9.6	9.6	9.6	9.6	9.5	9.4	46
48	6.7	7.1	7.3	7.6	7.9	8.2	8.5	8.8	9.2	9.3	9.4	9.4	9.4	9.4	9.4	9.1	48
50	6.4	6.7	7.1	7.3	7.6	7.9	8.2	8.5	8.9	9.1	9.2	9.2	9.2	9.2	9.2	8.8	50
52	6.2	6.5	6.8	7.1	7.3	7.6	7.9	8.2	8.5	8.8	9.0	9.1	9.1	9.0	9.0	8.6	52
54	6.0	6.2	6.5	6.8	7.1	7.3	7.6	7.9	8.2	8.5	8.8	8.9	8.9	8.9	8.9	8.4	54
56		6.1	6.3	6.5	6.8	7.1	7.3	7.6	7.9	8.1	8.6	8.7	8.8	8.7	8.7	8.2	56
58		5.8	6.1	6.3	6.6	6.8	7.0	7.2	7.4	7.7	8.5	8.6	8.6	8.4	8.2	7.9	58
60			5.9	6.1	6.4	6.6	6.8	7.0	7.2	7.4	8.2	8.3	8.1	7.8	7.6	7.4	60
62				5.9	6.2	6.4	6.6	6.8	7.0	7.2	7.9	7.8	7.5	7.3	7.1	6.9	62
64					6.0	6.2	6.4	6.6	6.8	7.0	7.5	7.3	7.1	6.8	6.6	6.4	64
66					5.8	6.1	6.3	6.5	6.6	6.8	7.1	6.8	6.6	6.4	6.2	5.9	66
68						5.9	6.1	6.3	6.5	6.6	6.6	6.4	6.2	5.9	5.7	5.5	68
70							5.9	6.1	6.3	6.3	6.2	6.0	5.8	5.5	5.3	5.1	70
72								5.8	6.1	6.0	5.8	5.6	5.4	5.1	4.9	4.7	72
74									5.9	5.7	5.5	5.2	5.0	4.8	4.6	4.3	74
76									5.6	5.3	5.1	4.9	4.7	4.4	4.2	4.0	76
78										5.0	4.8	4.6	4.4	4.1	3.9	3.7	78
80											4.5	4.3	4.0	3.8	3.6	3.3	80
82												4.0	3.7	3.5	3.3	3.0	82
84													3.7	3.5	3.2	2.8	84
86														2.9	2.8	2.6	86
88															2.7	2.5	88
90																2.2	90
92																2.0	92
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	Parts of line

Unit: t

**FJ Load Chart**

Load chart –FJa( Aux. hook, boom 28~73m) 5/8																	
Jib 13m, Boom to jib angle 30°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
16	17.6	17.8															16
18	17.0	17.1	17.4	17.5	17.6	17.7											18
20	16.4	16.6	16.8	17.0	17.1	17.2	17.3	17.4	17.4	17.6							20
22	15.7	15.9	16.3	16.4	16.7	16.8	16.9	17.0	17.0	17.1	17.1	17.3	17.3	17.3			22
24	15.1	15.3	15.8	16.0	16.1	16.3	16.4	16.5	16.7	16.8	16.8	16.9	16.9	16.9	17.0	17.0	24
26	14.7	14.9	15.1	15.4	15.7	15.9	16.1	16.2	16.3	16.4	16.4	16.5	16.7	16.7	16.7	16.6	26
28	14.2	14.4	14.6	14.8	15.0	15.5	15.7	15.8	15.9	16.1	16.2	16.3	16.3	16.4	16.4	16.4	28
30	13.8	14.0	14.2	14.4	14.6	15.1	15.3	15.5	15.7	15.8	15.9	16.0	16.0	16.1	16.1	16.1	30
32	13.5	13.7	13.9	14.1	14.3	14.7	14.9	15.2	15.3	15.5	15.6	15.7	15.7	15.8	15.8	15.9	32
34	13.2	13.4	13.6	13.8	14.0	14.2	14.4	14.6	14.8	15.1	15.3	15.5	15.6	15.5	15.6	15.7	34
36	12.8	13.0	13.2	13.4	13.6	13.8	14.0	14.2	14.4	14.6	14.9	15.2	15.3	15.0	15.1	14.7	36
38	12.5	12.7	12.9	13.1	13.3	13.5	13.7	13.9	14.1	14.3	14.5	14.9	14.7	14.3	14.1	13.7	38
40		12.4	12.6	12.8	13.0	13.2	13.4	13.6	13.8	14.0	14.2	14.4	14.4	13.5	13.2	12.8	40
42		12.1	12.3	12.5	12.7	12.9	13.1	13.3	13.5	13.7	13.9	14.1	13.9	13.2	12.3	11.9	42
44			12.0	12.2	12.4	12.6	12.8	13.0	13.2	13.3	13.4	13.5	13.4	12.7	11.9	11.2	44
46				11.9	12.1	12.3	12.5	12.7	12.8	12.7	12.6	12.6	12.4	12.2	11.7	10.6	46
48					11.9	12.1	12.3	12.2	12.2	12.0	11.9	11.7	11.6	11.4	11.2	10.3	48
50						11.9	11.8	11.6	11.5	11.3	11.1	10.9	10.8	10.6	10.4	10.0	50
52							11.2	11.1	10.9	10.7	10.5	10.4	10.2	10.0	9.8	9.5	52
54								10.4	10.2	10.1	9.9	9.7	9.5	9.4	9.2	8.8	54
56									9.6	9.4	9.2	9.1	8.9	8.7	8.5	8.1	56
58										8.8	8.7	8.5	8.3	8.1	7.9	7.5	58
60											8.3	8.1	8.0	7.7	7.5	7.1	60
62												7.6	7.4	7.2	7.0	6.6	62
64													6.9	6.7	6.5	6.1	64
66														6.2	6.0	5.6	66
68															5.7	5.3	68
70																5.1	70
72																	72
74																	74
76																	76
78																	78
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	Parts of line

# FJ Load Chart

Load chart -FJa( Aux. hook, boom 28~73m) 6/8																	
Jib 19m, Boom to jib angle 30°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
20	12.1	12.3															20
22	11.7	11.8	12.0	12.1	12.2	12.2											22
24	11.3	11.4	11.6	11.7	11.8	11.9	12.0	12.0	12.1	12.1							24
26	10.8	11.1	11.2	11.3	11.5	11.5	11.7	11.7	11.8	11.8	11.9	11.9	12.0	12.1			26
28	10.4	10.7	10.8	11.0	11.1	11.2	11.4	11.4	11.6	11.6	11.7	11.7	11.8	11.8	11.8	11.9	28
30	10.0	10.3	10.4	10.7	10.8	10.9	11.1	11.2	11.3	11.3	11.4	11.5	11.6	11.6	11.6	11.6	30
32	9.6	9.8	10.0	10.4	10.6	10.7	10.8	10.9	11.0	11.1	11.2	11.2	11.3	11.4	11.4	11.5	32
34	9.4	9.5	9.6	10.1	10.3	10.4	10.6	10.7	10.7	10.9	10.9	11.0	11.1	11.2	11.2	11.2	34
36	9.1	9.2	9.3	9.7	10.0	10.2	10.4	10.5	10.5	10.7	10.7	10.9	10.9	11.0	11.0	11.1	36
38	8.9	9.0	9.1	9.4	9.7	10.0	10.1	10.3	10.4	10.4	10.6	10.7	10.7	10.8	10.9	10.9	38
40	8.6	8.7	8.8	9.2	9.4	9.7	9.9	10.0	10.2	10.2	10.4	10.4	10.6	10.6	10.6	10.7	40
42	8.3	8.4	8.5	8.8	9.2	9.5	9.7	9.9	10.0	10.1	10.2	10.3	10.3	10.5	10.5	10.6	42
44	8.2	8.3	8.4	8.7	9.0	9.3	9.6	9.7	9.9	9.9	10.0	10.1	10.2	10.2	10.4	10.4	44
46		8.2	8.3	8.6	8.9	9.1	9.4	9.6	9.7	9.8	9.9	9.9	10.1	10.1	10.2	10.2	46
48		8.1	8.2	8.5	8.8	9.0	9.2	9.4	9.5	9.6	9.8	9.8	9.9	10.0	10.0	9.9	48
50			8.1	8.4	8.7	8.9	9.0	9.1	9.4	9.5	9.6	9.7	9.8	9.8	9.9	10.0	50
52				8.3	8.6	8.8	8.9	9.0	9.3	9.4	9.5	9.6	9.7	9.7	9.8	9.9	52
54					8.5	8.7	8.8	8.9	9.2	9.3	9.4	9.5	9.5	9.6	9.5	9.3	54
56						8.6	8.7	8.8	9.0	9.2	9.2	9.3	9.2	9.0	8.9	8.7	56
58							8.5	8.6	8.7	8.8	8.9	8.9	8.7	8.6	8.4	8.0	58
60								8.5	8.6	8.6	8.5	8.4	8.2	8.0	7.8	7.4	60
62									8.3	8.2	8.0	7.9	7.7	7.5	7.3	6.9	62
64										7.7	7.5	7.4	7.1	7.0	6.7	6.4	64
66											7.2	7.0	6.9	6.7	6.5	6.1	66
68												6.5	6.4	6.2	6.0	5.8	68
70													6.0	5.8	5.6	5.3	70
72														5.3	5.2	4.9	72
74															4.9	4.8	74
76																4.4	76
78																	78
80																	80
82																	82
84																	84
Counter weight(t) Parts of line	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t) Parts of line
	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	

Unit: t


### FJ Load Chart

Load chart -FJa( Aux. hook, boom 28~73m) 7/8																	
Jib 25m, Boom to jib angle 30°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
24	8.6	8.7															24
26	8.3	8.4	8.5	8.6	8.6	8.7											26
28	8.0	8.1	8.2	8.3	8.3	8.4	8.5	8.5	8.6	8.6							28
30	7.7	7.8	7.9	8.0	8.1	8.2	8.2	8.3	8.4	8.4	8.4	8.4	8.5	8.5			30
32	7.4	7.5	7.6	7.8	7.9	7.9	8.0	8.1	8.1	8.2	8.2	8.3	8.3	8.3	8.4	8.4	32
34	7.1	7.3	7.4	7.5	7.6	7.7	7.8	7.9	7.9	8.0	8.0	8.1	8.1	8.2	8.2	8.3	34
36	7.0	7.1	7.2	7.3	7.4	7.5	7.6	7.7	7.8	7.8	7.9	7.9	8.0	8.0	8.0	8.1	36
38	6.8	6.9	7.1	7.1	7.3	7.3	7.4	7.5	7.6	7.6	7.7	7.8	7.8	7.9	7.9	7.9	38
40	6.6	6.7	6.9	7.0	7.1	7.2	7.3	7.3	7.4	7.5	7.5	7.6	7.7	7.7	7.8	7.8	40
42	6.5	6.6	6.7	6.8	6.9	7.0	7.1	7.2	7.3	7.4	7.4	7.5	7.5	7.6	7.6	7.7	42
44	6.3	6.4	6.6	6.7	6.8	6.9	7.0	7.1	7.2	7.2	7.2	7.3	7.4	7.5	7.5	7.6	44
46	6.2	6.3	6.4	6.5	6.7	6.7	6.8	6.9	7.0	7.1	7.1	7.2	7.3	7.3	7.4	7.4	46
48	6.2	6.2	6.3	6.4	6.5	6.6	6.7	6.8	6.9	6.9	7.0	7.1	7.2	7.2	7.2	7.3	48
50	6.1	6.2	6.2	6.3	6.4	6.5	6.6	6.7	6.7	6.8	6.9	7.0	7.0	7.1	7.1	7.2	50
52		6.1	6.2	6.2	6.3	6.4	6.5	6.6	6.7	6.7	6.8	6.8	6.9	7.0	7.0	7.1	52
54		6.2	6.1	6.2	6.2	6.3	6.4	6.4	6.5	6.6	6.7	6.7	6.8	6.9	6.9	7.0	54
56			6.1	6.1	6.2	6.2	6.3	6.3	6.4	6.5	6.6	6.7	6.7	6.8	6.9	6.9	56
58				6.1	6.1	6.2	6.2	6.3	6.3	6.4	6.5	6.6	6.6	6.7	6.8	6.8	58
60					6.1	6.1	6.2	6.2	6.3	6.4	6.4	6.5	6.5	6.6	6.7	6.7	60
62						6.1	6.1	6.2	6.2	6.3	6.4	6.4	6.4	6.5	6.6	6.7	62
64							6.1	6.1	6.1	6.2	6.3	6.3	6.3	6.4	6.4	6.5	64
66								6.1	6.1	6.1	6.2	6.2	6.3	6.3	6.3	6.4	66
68									6.1	6.1	6.1	6.2	6.2	6.2	6.1	6.0	68
70										6.1	6.1	6.1	6.1	6.0	5.7	5.4	70
72											6.2	6.0	5.9	5.7	5.5	5.0	72
74												5.6	5.5	5.3	4.8	4.6	74
76													5.1	4.9	4.4	4.2	76
78														4.6	4.0	3.8	78
80															4.2	3.5	80
82																3.4	82
84																2.8	84
86																	86
88																	88
Counter weight(t) Parts of line	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t) Parts of line
	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	


## FJ Load Chart

Load chart -FJa( Aux. hook, boom 28~73m) 8/8																	
Jib 31m, Boom to jib angle 30°																	
Jib length (m) Radius (m)	28	31	34	37	40	43	46	49	52	55	58	61	64	67	70	73	Jib length (m) Radius (m)
28	6.2	6.3															28
30	6.0	6.1	6.2	6.2	6.2	6.3											30
32	5.8	5.8	5.9	6.0	6.0	6.1	6.2	6.2	6.2	6.2							32
34	5.6	5.7	5.7	5.8	5.9	5.9	5.9	6.0	6.0	6.1	6.1	6.2	6.2	6.2			34
36	5.4	5.4	5.5	5.6	5.7	5.7	5.8	5.8	5.9	5.9	6.0	6.0	6.1	6.1	6.1	6.1	36
38	5.2	5.3	5.4	5.4	5.5	5.6	5.6	5.7	5.8	5.8	5.9	5.9	5.9	6.0	6.0	6.0	38
40	5.0	5.1	5.2	5.3	5.4	5.4	5.5	5.6	5.6	5.7	5.7	5.7	5.8	5.8	5.9	5.8	40
42	4.8	5.0	5.1	5.2	5.2	5.3	5.4	5.4	5.5	5.6	5.6	5.6	5.7	5.7	5.7	5.8	42
44	4.7	4.8	4.9	5.0	5.1	5.2	5.2	5.3	5.3	5.4	5.4	5.5	5.5	5.6	5.6	5.6	44
46	4.6	4.7	4.8	4.9	4.9	5.0	5.1	5.2	5.2	5.3	5.3	5.4	5.4	5.4	5.5	5.5	46
48	4.5	4.6	4.7	4.8	4.8	4.9	5.0	5.0	5.1	5.2	5.2	5.3	5.3	5.4	5.4	5.4	48
50	4.4	4.5	4.6	4.7	4.7	4.8	4.9	4.9	5.0	5.1	5.1	5.2	5.2	5.3	5.3	5.3	50
52	4.3	4.4	4.5	4.6	4.6	4.7	4.8	4.9	4.9	5.0	5.0	5.1	5.1	5.2	5.2	5.3	52
54	4.2	4.3	4.4	4.5	4.6	4.6	4.7	4.8	4.8	4.9	4.9	5.0	5.0	5.1	5.1	5.2	54
56	4.2	4.2	4.4	4.4	4.5	4.5	4.6	4.7	4.8	4.8	4.9	4.9	5.0	5.0	5.1	5.1	56
58		4.2	4.2	4.4	4.4	4.4	4.5	4.6	4.6	4.7	4.8	4.8	4.9	4.9	4.9	5.0	58
60		4.3	4.2	4.3	4.4	4.4	4.4	4.5	4.6	4.6	4.7	4.7	4.8	4.8	4.9	4.9	60
62			4.3	4.2	4.3	4.4	4.4	4.4	4.5	4.5	4.6	4.7	4.7	4.8	4.8	4.9	62
64				4.3	4.2	4.3	4.4	4.4	4.4	4.5	4.5	4.6	4.6	4.7	4.8	4.8	64
66					4.2	4.2	4.3	4.4	4.4	4.4	4.5	4.5	4.6	4.6	4.7	4.7	66
68						4.2	4.2	4.3	4.3	4.4	4.4	4.5	4.5	4.6	4.6	4.6	68
70						4.3	4.2	4.2	4.3	4.3	4.4	4.4	4.5	4.5	4.6	4.6	70
72							4.3	4.2	4.2	4.3	4.3	4.4	4.4	4.5	4.5	4.5	72
74								4.3	4.2	4.2	4.3	4.3	4.4	4.4	4.5	4.5	74
76									4.2	4.2	4.2	4.3	4.3	4.4	4.4	4.5	76
78									4.3	4.2	4.2	4.2	4.3	4.3	4.4	4.2	78
80										4.3	4.2	4.2	4.3	4.2	4.0	3.8	80
82												4.0	3.9	3.9	3.6	3.4	82
84												3.9	3.7	3.5	3.4	3.2	84
86													3.4	3.2	3.1	2.8	86
88													3.1	2.9	2.8	2.6	88
Counter weight(t) Parts of line	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t) Parts of line
	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	


## LJ Configuration



Note: ★ means recommended jib combination for purchasing.



## LJ Working Radius



Unit: t

## LJ Load Chart

**Note:**

- 1.The rated load in the load chart is calculated complying with EN 13000;
- 2.The working radius is the horizontal distance from the load center to the swing center;
- 3.The actual lifting capacity must subtract the weight of hooks and other riggings from the rated capacity in the load chart.
- 4.The load value is calculated when the object is hung freely,without considering the influence of wind on the load, ground conditions and slope, operation speed and the influence of any other negative factors over safe operation. Therefore, the operator bears the responsibility of making a judgement and decreasing the load and lowering speed.
- 5.All ratings are calculated when the machine is parking on firm and level ground with less than 1% gradient.

### Load chart –LJ(Aux. hook) 1/12

Boom 25m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
12	63.0	61.5												12
14	52.7	53.0	54.3	49.9										14
16	43.1	43.4	44.5	44.4	44.2	38.6	33.6							16
18	36.4	36.6	37.6	37.4	37.3	37.2	33.3	29.1	25.5					18
20	31.4	31.6	32.5	32.3	32.2	32.1	31.9	28.7	25.1	22.1	19.5			20
22	27.6	27.7	28.5	28.4	28.3	28.1	27.9	27.8	24.8	21.7	19.1	16.8	14.8	22
24	24.5	24.7	25.4	25.2	25.1	25.0	24.8	24.7	24.4	21.3	18.7	16.5	14.5	24
26		22.2	22.8	22.7	22.6	22.4	22.3	22.1	22.0	21.0	18.4	16.1	14.1	26
28		18.5	20.7	20.6	20.5	20.3	20.2	20.0	19.9	19.7	18.0	15.7	13.8	28
30			18.1	18.8	18.7	18.5	18.4	18.2	18.1	18.0	17.6	15.4	13.4	30
32				17.2	17.1	17.0	16.8	16.7	16.6	16.4	16.3	15.0	13.1	32
34				13.4	15.8	15.7	15.5	15.4	15.3	15.1	15.0	14.7	12.8	34
36					13.2	14.5	14.4	14.3	14.1	14.0	13.8	13.7	12.5	36
38						12.8	13.4	13.3	13.1	13.0	12.8	12.7	12.1	38
40						10.1	12.3	12.4	12.2	12.1	11.9	11.8	11.6	40
44								9.7	10.7	10.5	10.4	10.3	10.1	44
48									7.6	8.9	9.2	9.0	8.7	48
52										5.8	7.1	7.8	7.4	52
56												5.5	6.1	56
60													4.2	60
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	5	5	5	4	4	3	3	3	2	2	2	2	2	Parts of line

**LJ Load Chart**

Load chart –LJ(Aux. hook) 2/12

Load chart –LJ(Aux. hook) 2/12														
Boom 28m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
12	61.2													12
14	53.8	54.9	55.3	49.8										14
16	44.4	44.6	46.0	46.0	43.1	37.4								16
18	37.3	37.5	38.6	38.6	38.6	37.2	32.4	28.4	24.9					18
20	32.1	32.3	33.2	33.2	33.2	33.1	32.1	28.1	24.6	21.7	19.1			20
22	28.1	28.3	29.1	29.0	29.0	28.9	28.8	27.7	24.3	21.3	18.8	16.6	14.6	22
24	25.0	25.1	25.8	25.7	25.7	25.6	25.5	25.4	23.9	21.0	18.4	16.2	14.3	24
26	20.6	22.5	23.2	23.1	23.1	23.0	22.8	22.7	22.6	20.6	18.1	15.9	14.0	26
28		20.4	21.0	20.9	20.9	20.8	20.7	20.5	20.4	20.2	17.7	15.5	13.6	28
30			19.1	19.1	19.0	18.9	18.8	18.7	18.5	18.4	17.4	15.2	13.3	30
32			14.7	17.5	17.4	17.3	17.2	17.1	17.0	16.8	16.7	14.9	13.0	32
34				14.8	16.1	16.0	15.9	15.8	15.6	15.5	15.3	14.5	12.7	34
36					14.5	14.8	14.7	14.6	14.4	14.3	14.2	14.0	12.4	36
38						13.7	13.6	13.5	13.4	13.2	13.1	13.0	12.1	38
40						11.1	12.7	12.6	12.5	12.3	12.2	12.1	11.8	40
44								10.7	10.9	10.8	10.6	10.5	10.3	44
48									8.4	9.5	9.4	9.2	9.1	48
52										6.5	7.9	8.2	7.7	52
56												6.2	6.4	56
60													4.8	60
Counter weight(t) Parts of line	74+25 5	74+25 5	74+25 5	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

Load chart -LJ(Aux. hook) 3/12														
Boom 31m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
12	60.5													12
14	55.2	55.4	54.0											14
16	45.7	46.0	47.4	47.4	41.4	36.1								16
18	38.3	38.5	39.6	39.6	39.6	35.9	31.4	27.6						18
20	32.8	33.0	34.0	33.9	33.9	33.9	31.2	27.3	24.0	21.2	18.8			20
22	28.7	28.8	29.7	29.6	29.6	29.5	29.4	27.0	23.7	20.9	18.4	16.3	14.4	22
24	25.4	25.5	26.3	26.2	26.2	26.1	26.0	25.9	23.4	20.6	18.1	16.0	14.1	24
26	22.8	22.9	23.6	23.5	23.4	23.4	23.2	23.2	23.1	20.2	17.8	15.6	13.7	26
28		20.7	21.3	21.2	21.2	21.1	21.0	20.9	20.8	19.9	17.5	15.3	13.4	28
30			19.4	19.3	19.3	19.2	19.1	19.0	18.9	18.7	17.1	15.0	13.2	30
32			16.3	17.7	17.7	17.6	17.4	17.4	17.3	17.1	16.8	14.7	12.9	32
34				16.1	16.3	16.2	16.1	16.0	15.9	15.7	15.6	14.4	12.5	34
36					15.1	15.0	14.8	14.7	14.6	14.5	14.4	14.1	12.2	36
38					12.1	13.9	13.8	13.7	13.6	13.4	13.3	13.2	12.0	38
40						12.2	12.8	12.7	12.6	12.5	12.4	12.3	11.7	40
44								11.1	11.0	10.9	10.8	10.7	10.5	44
48									9.1	9.6	9.5	9.4	9.2	48
52										7.1	8.4	8.3	7.8	52
56												6.8	6.6	56
60													5.3	60
Counter weight(t) Parts of line	74+25 5	74+25 5	74+25 4	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	Counter weight(t) Parts of line

# LJ Load Chart

Load chart -LJ(Aux. hook) 4/12

Load chart -LJ(Aux. hook) 4/12														
Boom 34m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
12	60.0													12
14	53.2	53.4	51.8											14
16	47.1	47.4	47.0	45.3	39.7	34.8								16
18	39.3	39.5	40.7	40.6	39.5	34.6	30.4	26.8						18
20	33.6	33.8	34.7	34.7	34.7	34.4	30.1	26.5	23.4	20.7				20
22	29.3	29.4	30.3	30.2	30.2	30.1	29.9	26.2	23.1	20.4	18.0	15.9	14.1	22
24	25.9	26.0	26.8	26.7	26.7	26.6	26.5	25.9	22.8	20.1	17.7	15.6	13.8	24
26	23.2	23.3	23.9	23.9	23.8	23.8	23.6	23.6	22.5	19.8	17.4	15.4	13.5	26
28		21.0	21.6	21.5	21.5	21.4	21.3	21.2	21.1	19.5	17.1	15.1	13.3	28
30			19.7	19.6	19.5	19.5	19.3	19.3	19.2	19.0	16.8	14.8	13.0	30
32			17.5	17.9	17.9	17.8	17.7	17.6	17.5	17.4	16.5	14.5	12.7	32
34				16.5	16.5	16.4	16.3	16.2	16.1	15.9	15.8	14.2	12.4	34
36					15.2	15.1	15.0	14.9	14.8	14.7	14.6	13.9	12.1	36
38					13.1	14.1	13.9	13.8	13.7	13.6	13.5	13.4	11.8	38
40						13.0	13.0	12.9	12.8	12.6	12.5	12.4	11.6	40
44							10.0	11.3	11.1	11.0	10.9	10.8	10.6	44
48									9.8	9.7	9.6	9.4	9.3	48
52										7.7	8.5	8.4	8.0	52
56												7.1	6.7	56
60													5.6	60
Counter weight(t) Parts of line	74+25 5	74+25 4	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

Load chart -LJ(Aux. hook) 5/12														
Boom 37m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	53.1	51.8	49.1											14
16	47.6	46.7	45.9	42.9	37.8									16
18	40.3	40.6	41.7	40.8	37.6	33.2	29.2	25.9						18
20	34.4	34.5	35.6	35.5	35.5	32.9	29.0	25.7	22.7	20.1				20
22	29.9	30.0	30.9	30.8	30.8	30.8	28.8	25.4	22.5	19.8	17.6	15.6		22
24	26.4	26.5	27.3	27.2	27.2	27.1	27.0	25.2	22.2	19.6	17.3	15.3	13.5	24
26	23.6	23.7	24.3	24.3	24.2	24.2	24.0	24.0	21.9	19.3	17.0	15.0	13.3	26
28		21.4	22.0	21.9	21.8	21.8	21.6	21.6	21.5	19.0	16.8	14.8	13.0	28
30		18.8	20.0	19.9	19.8	19.7	19.6	19.5	19.4	18.7	16.5	14.5	12.7	30
32			18.3	18.2	18.1	18.1	17.9	17.8	17.7	17.6	16.2	14.2	12.5	32
34				16.7	16.7	16.6	16.5	16.4	16.3	16.1	15.9	13.9	12.2	34
36					15.4	15.3	15.2	15.1	15.0	14.9	14.8	13.7	11.9	36
38					14.0	14.2	14.1	14.0	13.9	13.8	13.6	13.4	11.7	38
40						13.2	13.1	13.0	12.9	12.8	12.7	12.5	11.4	40
44							10.8	11.4	11.3	11.1	11.0	10.9	10.7	44
48									9.9	9.8	9.7	9.5	9.4	48
52										8.2	8.6	8.4	8.2	52
56											6.4	7.4	6.9	56
60													5.7	60
Counter weight(t) Parts of line	74+25 4	74+25 4	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	Counter weight(t) Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 6/12**

Load chart –LJ(Aux. hook) 6/12														
Boom 40m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	51.1	49.8												14
16	46.2	45.3	44.1	40.6	36.0									16
18	41.5	41.0	40.3	39.4	35.8	31.7	28.1							18
20	35.2	35.4	36.4	36.1	35.4	31.4	27.9	24.7	22.0	19.5				20
22	30.5	30.7	31.6	31.5	31.5	31.1	27.7	24.5	21.7	19.3	17.1	15.2		22
24	26.9	27.0	27.8	27.7	27.7	27.6	27.4	24.3	21.5	19.0	16.8	14.9	13.2	24
26	24.0	24.1	24.8	24.7	24.7	24.6	24.5	24.0	21.2	18.8	16.6	14.7	13.0	26
28		21.7	22.3	22.2	22.2	22.1	22.0	21.9	21.0	18.5	16.3	14.4	12.7	28
30		19.7	20.3	20.2	20.1	20.0	19.9	19.8	19.7	18.2	16.1	14.2	12.5	30
32			18.5	18.4	18.4	18.3	18.2	18.1	18.0	17.9	15.8	13.9	12.2	32
34				17.0	16.9	16.8	16.7	16.6	16.5	16.4	15.6	13.7	12.0	34
36				15.0	15.6	15.5	15.4	15.3	15.2	15.1	14.9	13.4	11.7	36
38					14.5	14.4	14.3	14.2	14.1	13.9	13.8	13.2	11.5	38
40						13.4	13.3	13.2	13.1	12.9	12.8	12.7	11.2	40
44							11.5	11.5	11.4	11.2	11.1	11.0	10.8	44
48									10.0	9.9	9.8	9.6	9.5	48
52										8.7	8.6	8.5	8.3	52
56											6.8	7.6	7.0	56
60													5.8	60
Counter weight(t) Parts of line	74+25 4	74+25 4	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

Load chart -LJ(Aux. hook) 7/12														
Boom 43m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	49.7	48.5												14
16	45.0	43.9	42.9	38.2										16
18	40.6	40.0	39.2	37.8	33.9	30.2	26.9							18
20	36.0	36.2	35.9	35.3	33.6	30.0	26.7	23.8	21.1					20
22	31.2	31.3	32.2	32.2	31.9	29.7	26.4	23.5	20.9	18.6	16.5	14.7		22
24	27.4	27.5	28.3	28.3	28.2	28.2	26.1	23.3	20.7	18.4	16.3	14.5	12.9	24
26	24.4	24.5	25.2	25.1	25.1	25.0	24.9	23.0	20.5	18.1	16.1	14.3	12.6	26
28		22.0	22.7	22.6	22.5	22.5	22.3	22.3	20.2	17.9	15.9	14.1	12.4	28
30		20.0	20.6	20.5	20.4	20.3	20.2	20.1	19.9	17.7	15.6	13.8	12.2	30
32			18.8	18.7	18.6	18.6	18.4	18.3	18.2	17.4	15.4	13.6	11.9	32
34				17.2	17.1	17.0	16.9	16.8	16.7	16.6	15.1	13.4	11.7	34
36				15.8	15.8	15.7	15.6	15.5	15.4	15.2	14.9	13.1	11.5	36
38					14.6	14.6	14.4	14.3	14.2	14.1	14.0	12.9	11.2	38
40						13.5	13.4	13.3	13.2	13.1	13.0	12.6	11.0	40
44							11.7	11.6	11.5	11.4	11.2	11.1	10.6	44
48								9.4	10.1	10.0	9.9	9.7	9.6	48
52										8.8	8.7	8.6	8.4	52
56											7.3	7.6	7.1	56
60													5.9	60
Counter weight(t) Parts of line	74+25 4	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	Counter weight(t) Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 8/12**

Load chart –LJ(Aux. hook) 8/12														
Boom 46m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	47.7	45.2												14
16	43.3	42.3	40.2	36.0										16
18	39.2	38.7	38.0	35.6	32.0	28.7								18
20	35.8	35.4	34.8	34.1	31.6	28.4	25.4	22.7	20.3					20
22	31.8	32.0	32.0	31.5	30.9	28.1	25.2	22.5	20.1	17.9	16.0			22
24	27.9	28.1	28.9	28.8	28.6	27.4	24.9	22.3	19.9	17.7	15.8	14.1	12.5	24
26	24.8	24.9	25.6	25.6	25.5	25.5	24.4	22.0	19.6	17.5	15.5	13.8	12.3	26
28	22.3	22.4	23.0	23.0	22.9	22.8	22.7	21.7	19.4	17.3	15.3	13.6	12.1	28
30		20.3	20.9	20.8	20.7	20.7	20.5	20.4	19.1	17.0	15.1	13.4	11.8	30
32			19.0	19.0	18.9	18.8	18.7	18.6	18.5	16.8	14.9	13.2	11.6	32
34				17.4	17.3	17.3	17.1	17.0	16.9	16.5	14.7	13.0	11.4	34
36				16.1	16.0	15.9	15.8	15.7	15.6	15.4	14.5	12.8	11.2	36
38					14.8	14.7	14.6	14.5	14.4	14.3	14.2	12.5	11.0	38
40						13.7	13.6	13.5	13.4	13.2	13.1	12.3	10.8	40
44							11.8	11.7	11.6	11.5	11.4	11.2	10.3	44
48								9.9	10.2	10.1	10.0	9.8	9.7	48
52										8.9	8.8	8.7	8.5	52
56											7.7	7.7	7.2	56
60												5.9	6.1	60
Counter weight(t) Parts of line	74+25 4	74+25 4	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

Load chart -LJ(Aux. hook) 9/12														
Boom 49m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	46.3													14
16	42.1	41.2	37.4	33.7										16
18	38.2	37.7	36.7	33.3	30.1	27.1								18
20	35.0	34.3	33.9	32.7	29.7	26.8	24.1	21.6						20
22	32.0	31.8	31.1	30.7	29.2	26.5	23.8	21.4	19.2	17.1	15.4			22
24	28.5	28.6	28.9	28.4	27.5	26.0	23.5	21.2	19.0	17.0	15.2	13.6	12.0	24
26	25.3	25.4	26.1	26.0	25.6	24.6	23.2	20.9	18.8	16.7	15.0	13.4	11.9	26
28	22.7	22.8	23.4	23.3	23.3	23.0	21.9	20.6	18.5	16.6	14.8	13.2	11.7	28
30		20.6	21.2	21.1	21.0	21.0	20.5	19.7	18.2	16.3	14.6	13.0	11.5	30
32			19.3	19.2	19.2	19.1	19.0	18.5	17.7	16.1	14.4	12.8	11.3	32
34			17.7	17.6	17.6	17.5	17.4	17.3	16.6	15.9	14.1	12.5	11.1	34
36				16.2	16.2	16.1	16.0	15.9	15.7	15.0	13.9	12.3	10.9	36
38					15.0	14.9	14.8	14.7	14.6	14.1	13.6	12.1	10.7	38
40					13.4	13.8	13.7	13.6	13.5	13.3	12.8	11.9	10.5	40
44							11.7	11.8	11.7	11.5	11.3	10.9	10.0	44
48								10.0	10.1	9.9	9.9	9.7	9.4	48
52										8.6	8.5	8.4	8.3	52
56											7.3	7.3	7.2	56
60												6.2	6.1	60
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	4	4	3	3	3	3	2	2	2	2	2	2	1	Parts of line

# LJ Load Chart

## Load chart -LJ(Aux. hook) 10/12

Boom 52m, Boom angle 84°

Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
14	42.7													14
16	40.4	38.2	34.8											16
18	37.0	36.3	34.1	31.0	28.2	25.5								18
20	33.9	33.3	32.7	30.4	27.8	25.2	22.7	20.5						20
22	31.1	30.7	30.2	29.4	27.3	24.8	22.5	20.3	18.3	16.4				22
24	28.8	28.4	28.0	27.4	26.2	24.4	22.1	20.0	18.1	16.2	14.5	13.0	11.6	24
26	25.7	25.8	26.0	25.5	24.6	23.4	21.8	19.8	17.9	16.0	14.4	12.8	11.4	26
28	23.0	23.1	23.8	23.5	22.9	21.9	21.0	19.4	17.6	15.8	14.2	12.6	11.2	28
30		20.9	21.5	21.4	21.1	20.5	19.7	18.8	17.3	15.6	14.0	12.4	11.0	30
32			19.6	19.5	19.4	19.0	18.4	17.8	17.0	15.3	13.8	12.3	10.9	32
34			17.9	17.9	17.8	17.6	17.1	16.7	16.0	15.1	13.5	12.1	10.7	34
36				16.4	16.3	16.2	15.9	15.5	15.1	14.4	13.3	11.9	10.5	36
38					15.0	14.9	14.6	14.5	14.1	13.6	13.1	11.7	10.3	38
40					13.7	13.7	13.6	13.5	13.2	12.8	12.4	11.4	10.1	40
44							11.5	11.5	11.4	11.2	11.0	10.6	9.7	44
48								9.8	9.8	9.7	9.6	9.4	9.1	48
52										8.4	8.3	8.2	8.1	52
56											7.2	7.1	7.1	56
60												6.2	6.2	60
Counter weight(t) Parts of line	74+25 4	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

Load chart -LJ(Aux. hook) 11/12														
Boom 55m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
16	38.2	35.2	32.2											16
18	36.0	34.2	31.5	28.8	26.3									18
20	33.1	32.5	30.7	28.2	25.9	23.6	21.4	19.4						20
22	30.4	29.9	29.2	27.5	25.3	23.2	21.1	19.2	17.3	15.6				22
24	28.1	27.8	27.1	26.1	24.7	22.7	20.8	18.9	17.1	15.4	13.8	12.4	11.1	24
26	26.0	25.7	25.0	24.2	23.2	22.3	20.4	18.6	16.9	15.2	13.7	12.2	10.9	26
28	23.4	23.4	22.9	22.3	21.6	20.9	19.9	18.3	16.6	15.0	13.5	12.1	10.8	28
30		21.2	20.9	20.5	20.2	19.5	18.8	17.9	16.3	14.7	13.3	11.9	10.6	30
32			19.1	18.8	18.5	18.1	17.6	16.9	16.0	14.5	13.1	11.7	10.4	32
34			17.5	17.2	17.0	16.8	16.4	15.8	15.3	14.2	12.9	11.5	10.2	34
36				15.8	15.6	15.5	15.2	14.8	14.4	13.8	12.6	11.3	10.1	36
38					14.4	14.3	14.1	13.8	13.5	13.0	12.4	11.1	9.9	38
40					13.7	13.6	13.5	12.8	12.6	12.2	11.8	10.9	9.7	40
44							11.1	11.0	10.9	10.7	10.5	10.1	9.3	44
48								9.4	9.3	9.3	9.1	8.9	8.7	48
52									8.0	8.0	7.9	7.8	7.7	52
56											6.9	6.8	6.7	56
60												5.9	5.9	60
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	3	3	3	3	2	2	2	2	2	2	2	1	1	Parts of line

## LJ Load Chart

Load chart -LJ(Aux. hook) 12/12

Load chart -LJ(Aux. hook) 12/12														
Boom 58m, Boom angle 84°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
16	35.2	32.5												16
18	33.9	31.6	29.2	26.8	24.6									18
20	31.9	30.4	28.3	26.2	24.1	22.1	20.1							20
22	29.4	29.0	27.4	25.5	23.6	21.7	19.8	18.0	16.3	14.7				22
24	27.3	26.9	25.9	24.7	23.0	21.2	19.4	17.7	16.1	14.5	13.1	11.8		24
26	25.3	24.7	24.0	23.2	22.2	20.7	19.0	17.4	15.9	14.3	12.9	11.7	10.4	26
28	23.1	22.7	22.2	21.6	20.8	20.1	18.6	17.1	15.6	14.1	12.8	11.5	10.2	28
30		20.7	20.4	19.9	19.4	18.8	18.1	16.7	15.3	13.9	12.6	11.3	10.1	30
32		19.0	18.7	18.4	18.0	17.5	16.9	16.3	15.0	13.6	12.4	11.1	9.9	32
34			17.1	16.8	16.6	16.2	15.8	15.4	14.7	13.4	12.2	10.9	9.7	34
36				15.5	15.3	15.1	14.7	14.3	13.8	13.1	11.9	10.7	9.6	36
38				14.2	14.1	14.0	13.7	13.4	13.0	12.5	11.7	10.5	9.4	38
40					12.9	12.9	12.7	12.5	12.2	11.8	11.4	10.3	9.2	40
44							10.9	10.8	10.6	10.4	10.1	9.8	8.8	44
48								9.3	9.2	9.0	8.9	8.7	8.4	48
52									7.9	7.8	7.8	7.6	7.5	52
56											6.8	6.7	6.6	56
60												5.8	5.7	60
64													5.0	64
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	74+25 1	Counter weight(t) Parts of line						

Unit: t

## LJ Load Chart

### Load chart -LJ(Aux. hook) 1/12

Load chart -LJ(Aux. hook) 1/12														
Boom 25m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
20	40.2	40.1												20
22	36.0	35.9	35.7	35.4										22
24	31.3	31.4	32.2	32.0	31.8									24
26	27.5	27.6	28.3	28.2	28.0	27.9	27.7							26
28	24.5	24.6	25.2	25.1	24.9	24.8	24.6	24.5						28
30		22.1	22.7	22.5	22.4	22.3	22.1	22.0	21.9	19.2				30
32		20.0	20.6	20.4	20.3	20.2	20.0	19.9	19.8	18.9	16.5			32
34			18.8	18.7	18.6	18.4	18.3	18.1	18.0	17.8	16.3	14.2	12.4	34
36				17.2	17.1	16.9	16.8	16.6	16.5	16.3	16.0	13.9	12.1	36
38				15.8	15.7	15.6	15.4	15.3	15.2	15.0	14.9	13.7	11.9	38
40					14.6	14.5	14.3	14.2	14.0	13.9	13.8	13.4	11.6	40
44						12.1	12.4	12.3	12.2	12.0	11.9	11.7	11.2	44
48							10.8	10.6	10.5	10.4	10.4	10.2	10.1	48
52								9.3	9.3	9.1	9.0	8.8	8.8	52
56											8.1	8.0	7.8	56
60												7.1	6.6	60
64													5.4	64
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	3	3	3	3	3	3	3	2	2	2	2	2	1	Parts of line

### Load chart -LJ(Aux. hook) 2/12

Load chart -LJ(Aux. hook) 2/12														
Boom 28m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
20	40.1													20
22	35.9	35.8	35.6											22
24	32.5	32.4	32.2	31.9	31.7									24
26	28.8	29.0	29.3	29.1	28.9	28.7								26
28	25.5	25.7	26.4	26.3	26.3	26.2	26.0	25.0						28
30	22.9	23.0	23.7	23.6	23.5	23.4	23.3	23.1	21.7					30
32		20.8	21.4	21.3	21.3	21.2	21.0	20.9	20.7	18.7	16.3			32
34			19.5	19.4	19.3	19.3	19.1	19.0	18.8	18.5	16.1	14.0		34
36			17.9	17.8	17.7	17.6	17.5	17.4	17.2	17.1	15.9	13.8	12.0	36
38				16.4	16.3	16.2	16.1	16.0	15.8	15.7	15.5	13.6	11.8	38
40					15.1	15.0	14.9	14.8	14.6	14.5	14.3	13.3	11.6	40
44						13.0	12.9	12.7	12.6	12.5	12.3	12.2	11.1	44
48							10.9	11.2	11.0	10.9	10.7	10.6	10.5	48
52									9.7	9.6	9.5	9.3	9.2	52
56										8.5	8.4	8.2	8.1	56
60												7.3	6.9	60
64													5.8	64
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	4	3	3	3	3	3	3	2	2	2	2	2	1	Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 3/12**

Load chart –LJ(Aux. hook) 3/12														
Boom 31m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
20	39.9													20
22	35.7	35.6												22
24	32.3	32.2	32.0	31.7										24
26	29.4	29.3	29.1	28.9	28.7	28.5								26
28	26.7	26.9	26.7	26.4	26.3	26.1	25.8							28
30	23.9	24.0	24.6	24.4	24.2	24.0	23.8	23.6	21.3					30
32		21.6	22.2	22.1	22.1	22.0	21.9	21.8	21.1	18.4				32
34		19.6	20.2	20.1	20.1	20.0	19.8	19.8	19.7	18.2	15.9	13.9		34
36			18.5	18.4	18.3	18.2	18.1	18.0	17.9	17.8	15.7	13.7	11.9	36
38				16.9	16.8	16.8	16.6	16.5	16.4	16.3	15.5	13.4	11.7	38
40				15.6	15.6	15.5	15.3	15.3	15.1	15.0	14.9	13.2	11.5	40
44						13.4	13.2	13.1	13.0	12.9	12.8	12.6	11.1	44
48						11.5	11.5	11.5	11.3	11.2	11.1	11.0	10.7	48
52									10.0	9.8	9.7	9.6	9.5	52
56										8.7	8.6	8.5	8.3	56
60											7.7	7.5	7.3	60
64													6.1	64
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	Counter weight(t) Parts of line

**Load chart –LJ(Aux. hook) 4/12**

Load chart –LJ(Aux. hook) 4/12														
Boom 34m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
22	35.5	35.4												22
24	32.1	32.0	31.8											24
26	29.3	29.1	28.9	28.7	28.5									26
28	26.9	26.7	26.5	26.3	26.1	25.9								28
30	24.8	24.7	24.5	24.2	24.1	23.9	23.6	23.4						30
32	22.4	22.5	22.7	22.4	22.3	22.1	21.8	21.7	20.7	18.1				32
34		20.4	20.9	20.8	20.7	20.5	20.3	20.1	19.9	17.9	15.7			34
36			19.1	19.0	19.0	18.9	18.8	18.7	18.5	17.7	15.5	13.5	11.8	36
38				17.4	17.4	17.3	17.2	17.1	17.0	16.8	15.3	13.3	11.6	38
40				16.1	16.0	15.9	15.8	15.7	15.6	15.5	15.1	13.1	11.4	40
44						13.7	13.6	13.5	13.4	13.3	13.1	12.7	11.0	44
48							11.8	11.8	11.6	11.5	11.4	11.3	10.6	48
52								10.3	10.2	10.1	10.0	9.9	9.7	52
56										8.9	8.8	8.7	8.6	56
60											7.8	7.7	7.6	60
64												6.9	6.4	64
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line

Unit: t

## LJ Load Chart

### Load chart -LJ(Aux. hook) 5/12

Boom 37m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
22	35.2													22
24	31.8	31.7	31.5											24
26	29.0	28.9	28.7	28.4										26
28	26.6	26.5	26.3	26.0	25.8	25.6								28
30	24.5	24.4	24.2	24.0	23.8	23.6	23.3							30
32	22.7	22.6	22.4	22.2	22.0	21.8	21.6	21.4	20.2					32
34		21.0	20.9	20.6	20.5	20.3	20.0	19.9	19.7	17.6	15.4			34
36			19.5	19.2	19.1	18.9	18.7	18.5	18.3	17.4	15.2	13.3		36
38			18.1	18.0	17.9	17.7	17.4	17.3	17.1	16.8	15.0	13.1	11.5	38
40				16.6	16.5	16.4	16.3	16.2	16.0	15.7	14.9	13.0	11.3	40
44					14.2	14.1	14.0	13.9	13.8	13.6	13.5	12.6	10.9	44
48							12.2	12.1	11.9	11.8	11.7	11.6	10.5	48
52								10.6	10.5	10.3	10.2	10.1	10.0	52
56									9.3	9.1	9.0	8.9	8.8	56
60											8.0	7.9	7.8	60
64												7.0	6.6	64
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line						

### Load chart -LJ(Aux. hook) 6/12

Boom 40m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
22	34.8													22
24	31.5	31.3												24
26	28.7	28.6	28.3	28.1										26
28	26.3	26.2	26.0	25.7	25.5									28
30	24.3	24.2	24.0	23.7	23.5	23.3	23.0							30
32	22.5	22.4	22.2	21.9	21.8	21.6	21.3	21.1						32
34		20.8	20.6	20.4	20.2	20.0	19.8	19.6	19.4	17.2				34
36		19.4	19.2	19.0	18.9	18.7	18.4	18.2	18.0	17.0	14.9	13.1		36
38			18.0	17.8	17.6	17.5	17.2	17.0	16.8	16.6	14.7	12.9	11.3	38
40				16.7	16.5	16.4	16.1	16.0	15.8	15.5	14.6	12.7	11.1	40
44					14.6	14.5	14.3	14.1	13.9	13.7	13.5	12.4	10.7	44
48						12.6	12.5	12.4	12.3	12.1	12.0	11.8	10.4	48
52								10.9	10.7	10.6	10.5	10.4	10.1	52
56									9.5	9.4	9.2	9.1	9.0	56
60											8.2	8.1	7.9	60
64												7.2	7.0	64
66													5.8	66
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line						

**LJ Load Chart****Load chart –LJ(Aux. hook) 7/12**

Load chart –LJ(Aux. hook) 7/12														
Boom 43m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
24	31.1	30.9												24
26	28.3	28.2	28.0											26
28	26.0	25.8	25.6	25.3	25.2									28
30	24.0	23.8	23.6	23.3	23.2	23.0								30
32	22.2	22.1	21.9	21.6	21.4	21.2	21.0	20.8						32
34	20.6	20.5	20.3	20.1	19.9	19.7	19.5	19.3	19.0					34
36		19.1	19.0	18.7	18.6	18.4	18.1	18.0	17.8	16.5	14.6			36
38			17.8	17.5	17.4	17.2	16.9	16.8	16.6	16.3	14.4	12.7	11.1	38
40			16.6	16.4	16.3	16.1	15.9	15.7	15.5	15.2	14.3	12.5	10.9	40
44					14.4	14.3	14.0	13.9	13.7	13.4	13.3	12.2	10.6	44
48						12.7	12.5	12.3	12.2	11.9	11.8	11.6	10.3	48
52								11.0	10.9	10.6	10.5	10.3	10.0	52
56									9.7	9.5	9.4	9.2	9.0	56
60										8.5	8.4	8.3	8.0	60
64												7.4	7.2	64
68													6.0	68
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line							

**Load chart –LJ(Aux. hook) 8/12**

Load chart –LJ(Aux. hook) 8/12														
Boom 46m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
24	30.7													24
26	28.0	27.8												26
28	25.7	25.5	25.3	25.0										28
30	23.7	23.5	23.3	23.0	22.9	22.7								30
32	21.9	21.8	21.6	21.3	21.2	21.0	20.7							32
34	20.4	20.3	20.1	19.8	19.7	19.5	19.2	19.0	18.3					34
36		18.9	18.7	18.5	18.3	18.1	17.9	17.7	17.5	16.0				36
38		17.7	17.5	17.3	17.1	17.0	16.7	16.5	16.3	15.9	14.0	12.4		38
40			16.4	16.2	16.1	15.9	15.6	15.5	15.3	15.0	13.9	12.2	10.7	40
44					14.2	14.1	13.8	13.7	13.5	13.2	13.0	11.9	10.4	44
48						12.5	12.3	12.1	12.0	11.7	11.5	11.4	10.1	48
52							11.0	10.9	10.7	10.5	10.3	10.1	9.8	52
56									9.6	9.4	9.2	9.0	8.8	56
60										8.4	8.3	8.1	7.9	60
64											7.4	7.3	7.1	64
68													6.2	68
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line								

Unit: t

## LJ Load Chart

### Load chart -LJ(Aux. hook) 9/12

Load chart -LJ(Aux. hook) 9/12														
Boom 49m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
26	27.6	27.4												26
28	25.3	25.1	24.9											28
30	23.3	23.2	22.9	22.7	22.5									30
32	21.6	21.5	21.3	21.0	20.8	20.6	20.3							32
34	20.1	20.0	19.8	19.5	19.3	19.1	18.8	18.6						34
36	18.7	18.6	18.4	18.2	18.0	17.8	17.5	17.3	17.1	15.5				36
38		17.4	17.2	17.0	16.8	16.6	16.4	16.2	16.0	15.4	13.6			38
40			16.2	15.9	15.8	15.6	15.3	15.2	15.0	14.7	13.5	11.9	10.4	40
44				14.1	14.0	13.8	13.5	13.4	13.2	12.9	12.7	11.6	10.1	44
48						12.3	12.1	11.9	11.7	11.5	11.3	11.1	9.9	48
52							10.8	10.6	10.5	10.2	10.1	9.9	9.6	52
56								9.5	9.4	9.2	9.0	8.8	8.6	56
60										8.2	8.1	7.9	7.7	60
64											7.3	7.1	6.9	64
68													6.2	68
Counter weight(t) Parts of line	74+25 3	74+25 3	74+25 2	74+25 1	74+25 1	Counter weight(t) Parts of line								

### Load chart -LJ(Aux. hook) 10/12

Load chart -LJ(Aux. hook) 10/12														
Boom 52m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
26	27.1													26
28	24.9	24.7	24.5											28
30	23.0	22.8	22.6	22.3										30
32	21.3	21.1	20.9	20.6	20.4	20.2								32
34	19.8	19.6	19.4	19.1	19.0	18.8	18.5	18.2						34
36	18.4	18.3	18.1	17.8	17.7	17.5	17.2	17.0	16.7					36
38		17.1	16.9	16.7	16.5	16.3	16.0	15.9	15.7	14.7	13.1			38
40			15.9	15.6	15.5	15.3	15.0	14.9	14.6	14.4	13.0	11.5		40
44				13.8	13.7	13.5	13.3	13.1	12.9	12.6	12.5	11.2	9.8	44
48					12.2	12.1	11.8	11.6	11.5	11.2	11.0	10.8	9.6	48
52							10.6	10.4	10.2	10.0	9.8	9.6	9.4	52
56								9.3	9.2	8.9	8.8	8.6	8.3	56
60									8.2	8.0	7.9	7.7	7.4	60
64											7.1	6.9	6.7	64
68												6.2	6.0	68
Counter weight(t) Parts of line	74+25 3	74+25 2	74+25 1	74+25 1	74+25 1	Counter weight(t) Parts of line								

**LJ Load Chart****Load chart –LJ(Aux. hook) 11/12**

Load chart –LJ(Aux. hook) 11/12														
Boom 55m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
26	26.6													26
28	24.4	24.2												28
30	22.5	22.4	22.1	21.7										30
32	20.9	20.7	20.5	20.2	19.9									32
34	19.4	19.3	19.0	18.7	18.6	18.3	17.9							34
36	18.1	18.0	17.8	17.5	17.3	17.1	16.8	16.5	15.8					36
38		16.8	16.6	16.3	16.2	16.0	15.7	15.5	15.2	14.0				38
40		15.7	15.6	15.3	15.2	15.0	14.7	14.5	14.3	13.9	12.4	11.0		40
44				13.6	13.4	13.2	13.0	12.8	12.6	12.3	12.1	10.8	9.5	44
48					11.9	11.8	11.5	11.4	11.2	10.9	10.7	10.5	9.3	48
52						10.5	10.3	10.2	10.0	9.7	9.5	9.3	9.1	52
56								9.1	8.9	8.7	8.5	8.3	8.1	56
60									8.0	7.8	7.6	7.5	7.2	60
64											6.9	6.7	6.4	64
68												6.0	5.8	68
72													5.1	72
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	2	2	2	1	1	1	Parts of line

**Load chart –LJ(Aux. hook) 12/12**

Load chart –LJ(Aux. hook) 12/12														
Boom 28m, Boom angle 75°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
28	23.9	23.6												28
30	22.1	21.9	21.5											30
32	20.5	20.3	20.1	19.7	19.4									32
34	19.1	18.9	18.7	18.4	18.1	17.8								34
36	17.8	17.6	17.4	17.1	17.0	16.7	16.3	16.0						36
38	16.6	16.5	16.3	16.0	15.9	15.7	15.3	15.0	14.7					38
40		15.5	15.3	15.0	14.9	14.7	14.4	14.2	13.9	13.1	11.8			40
44			13.5	13.3	13.1	13.0	12.7	12.5	12.3	12.0	11.6	10.3	9.0	44
48					11.7	11.5	11.3	11.1	10.9	10.6	10.5	10.1	8.8	48
52						10.3	10.1	9.9	9.7	9.5	9.3	9.1	8.7	52
56								8.9	8.7	8.5	8.3	8.1	7.8	56
60									7.8	7.6	7.4	7.2	7.0	60
64										6.8	6.7	6.5	6.2	64
68												5.8	5.6	68
72													5.0	72
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	2	2	1	1	1	1	Parts of line

Unit: t

## LJ Load Chart

### Load chart –LJ(Aux. hook) 1/12

Boom 25m, Boom angle 65°														
Jib length Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length Radius (m)
26	26.8													26
28	24.7	24.5												28
30	22.7	22.6	22.4											30
32	21.0	20.9	20.7	20.5										32
34	19.5	19.5	19.3	19.0	18.9									34
36		18.1	18.0	17.7	17.6	17.4	17.1							36
38			16.8	16.6	16.4	16.3	16.0	15.8						38
40				15.5	15.4	15.2	15.0	14.8	14.6					40
44					13.6	13.5	13.2	13.1	12.9	12.6	12.5			44
48						12.0	11.8	11.6	11.4	11.2	11.0	10.8	10.1	48
52								10.4	10.2	10.0	9.8	9.6	9.4	52
56									9.1	8.9	8.8	8.6	8.4	56
60										8.0	7.9	7.7	7.5	60
64												6.9	6.7	64
68													6.0	68
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	2	2	1	1	1	1	Parts of line

### Load chart –LJ(Aux. hook) 2/12

Boom 28m, Boom angle 65°														
Jib length Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length Radius (m)
28	24.4													28
30	22.5	22.3												30
32	20.8	20.7	20.4	20.2										32
34	19.3	19.2	19.0	18.7	18.6									34
36		17.9	17.7	17.5	17.3	17.1								36
38		16.7	16.6	16.3	16.2	16.0	15.7							38
40			15.5	15.3	15.2	15.0	14.7	14.5						40
44					13.4	13.2	13.0	12.8	12.6	12.4				44
48						11.8	11.5	11.4	11.2	11.0	10.8	10.6	10.0	48
52							10.3	10.2	10.0	9.8	9.6	9.4	9.2	52
56									9.0	8.7	8.6	8.4	8.1	56
60										7.8	7.7	7.5	7.3	60
64											6.9	6.7	6.5	64
68													5.8	68
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	2	2	2	1	1	1	Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 3/12**

Load chart –LJ(Aux. hook) 3/12														
Boom 31m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
30	22.0	21.9												30
32	20.4	20.3	20.0											32
34	19.0	18.8	18.6	18.3										34
36	17.7	17.6	17.4	17.1	16.9									36
38		16.4	16.2	16.0	15.8	15.6								38
40			15.2	15.0	14.8	14.6	14.4							40
44				13.2	13.1	12.9	12.7	12.5	12.3	12.0				44
48					11.6	11.5	11.3	11.1	10.9	10.7	10.5	10.3		48
52							10.1	9.9	9.7	9.5	9.3	9.1	8.9	52
56								8.9	8.7	8.5	8.3	8.1	7.9	56
60										7.6	7.4	7.3	7.0	60
64											6.7	6.5	6.3	64
68												5.8	5.6	68
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	1	1	1	1	1	1	Parts of line

**Load chart –LJ(Aux. hook) 4/12**

Load chart –LJ(Aux. hook) 4/12														
Boom 34m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
30	21.7													30
32	20.1	19.9												32
34	18.7	18.5	18.3											34
36	17.4	17.3	17.1	16.8										36
38		16.1	16.0	15.7	15.5	15.3								38
40		15.1	15.0	14.7	14.5	14.3	14.1							40
44				13.0	12.8	12.7	12.4	12.2	12.0					44
48					11.4	11.3	11.0	10.8	10.6	10.4	10.2			48
52						10.0	9.8	9.7	9.5	9.2	9.1	8.9	8.6	52
56								8.7	8.5	8.2	8.1	7.9	7.6	56
60									7.6	7.4	7.2	7.0	6.8	60
64											6.5	6.3	6.1	64
68												5.6	5.4	68
72													4.8	72
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	2	1	1	1	1	1	1	Parts of line

Unit: t

## LJ Load Chart

### Load chart -LJ(Aux. hook) 5/12

Boom 37m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
32	19.6													32
34	18.2	18.1												34
36	17.0	16.8	16.6	16.3										36
38	15.9	15.8	15.5	15.3	15.1									38
40		14.8	14.6	14.3	14.1	13.9								40
44			12.9	12.6	12.5	12.3	12.0	11.8						44
48					11.1	10.9	10.7	10.5	10.3	10.0	9.8			48
52						9.8	9.5	9.4	9.2	8.9	8.7	8.5	8.2	52
56							8.5	8.4	8.2	7.9	7.8	7.6	7.3	56
60									7.3	7.1	6.9	6.7	6.5	60
64										6.4	6.2	6.0	5.8	64
68											5.5	5.4	5.1	68
72													4.6	72
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	2	1	1	1	1	1	1	1	Parts of line

### Load chart -LJ(Aux. hook) 6/12

Boom 40m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
32	19.1													32
34	17.8	17.6												34
36	16.6	16.4	16.2											36
38	15.5	15.3	15.1	14.8										38
40	14.5	14.4	14.2	13.9	13.7									40
44			12.5	12.3	12.1	11.9	11.6	11.4						44
48				10.9	10.8	10.6	10.3	10.1	9.9	9.6				48
52						9.4	9.2	9.0	8.8	8.6	8.4	8.2		52
56							8.2	8.1	7.9	7.6	7.4	7.2	7.0	56
60								7.2	7.1	6.8	6.6	6.4	6.2	60
64										6.1	5.9	5.7	5.5	64
68											5.3	5.1	4.9	68
72												4.5	4.3	72
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	1	1	1	1	1	1	1	1	Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 7/12**

Load chart –LJ(Aux. hook) 7/12														
Boom 43m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
34	17.2													34
36	16.1	15.9												36
38	15.0	14.9	14.6											38
40	14.1	13.9	13.7	13.4										40
44		12.3	12.1	11.8	11.7	11.5	11.2							44
48				10.5	10.4	10.2	9.9	9.7	9.5					48
52					9.3	9.1	8.8	8.6	8.4	8.2	8.0			52
56						8.1	7.9	7.7	7.5	7.3	7.1	6.9	6.6	56
60								6.9	6.7	6.5	6.3	6.1	5.8	60
64									6.0	5.8	5.6	5.4	5.2	64
68											5.0	4.8	4.6	68
72												4.3	4.0	72
76													3.5	76
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	1	1	1	1	1	1	1	1	1	1	Parts of line

**Load chart –LJ(Aux. hook) 8/12**

Load chart –LJ(Aux. hook) 8/12														
Boom 46m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
36	15.6													36
38	14.6	14.4	14.2											38
40	13.7	13.5	13.3	13.0										40
44		12.0	11.8	11.5	11.3	11.1								44
48			10.4	10.2	10.0	9.8	9.5	9.3						48
52					8.9	8.8	8.5	8.3	8.1	7.8	7.6			52
56						7.8	7.6	7.4	7.2	6.9	6.7	6.5	6.3	56
60							6.8	6.6	6.4	6.2	6.0	5.8	5.5	60
64									5.8	5.5	5.3	5.1	4.9	64
68										4.9	4.7	4.5	4.3	68
72												4.0	3.8	72
76													3.3	76
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	2	2	2	1	1	1	1	1	1	1	1	Parts of line

Unit: t

## LJ Load Chart

### Load chart -LJ(Aux. hook) 9/12

Boom 49m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
36	15.1													36
38	14.1	13.9												38
40	13.2	13.0	12.8											40
44	11.6	11.5	11.3	11.0	10.8									44
48			10.0	9.8	9.6	9.4	9.1	8.9						48
52				8.7	8.6	8.4	8.1	7.9	7.7	7.4				52
56						7.5	7.2	7.0	6.8	6.5	6.3	6.1		56
60							6.4	6.3	6.1	5.8	5.6	5.4	5.1	60
64								5.6	5.4	5.2	5.0	4.8	4.5	64
68										4.6	4.4	4.2	4.0	68
72											3.9	3.7	3.5	72
76												3.2	3.0	76
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	2	1	1	1	1	1	1	1	1	1	1	1	Parts of line

### Load chart -LJ(Aux. hook) 10/12

Boom 52m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
38	13.6													38
40	12.7	12.5												40
44	11.2	11.1	10.8	10.5	10.3									44
48		9.8	9.6	9.3	9.2	8.9	8.6							48
52				8.3	8.2	8.0	7.7	7.5	7.3					52
56					7.3	7.1	6.8	6.6	6.4	6.1	5.9	5.7		56
60							6.1	5.9	5.7	5.4	5.2	5.0	4.7	60
64								5.3	5.1	4.8	4.6	4.4	4.2	64
68									4.5	4.3	4.1	3.9	3.6	68
72											3.6	3.4	3.1	72
76												3.0	2.7	76
80													2.3	80
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	2	1	1	1	1	1	1	1	1	1	1	1	1	Parts of line

**LJ Load Chart****Load chart –LJ(Aux. hook) 11/12**

Load chart –LJ(Aux. hook) 11/12														
Boom 55m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
40	12.1	11.9												40
44	10.7	10.5	10.3	10.0										44
48		9.4	9.2	8.9	8.7	8.4								48
52			8.1	7.9	7.7	7.5	7.2	7.0	6.8					52
56					6.9	6.7	6.4	6.2	6.0	5.7	5.5			56
60						6.0	5.7	5.5	5.3	5.0	4.8	4.6	4.3	60
64							5.1	4.9	4.7	4.4	4.2	4.0	3.8	64
68									4.2	3.9	3.7	3.5	3.2	68
72										3.4	3.3	3.1	2.8	72
76												2.6	2.4	76
80													2.0	80
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	1	1	1	1	1	1	1	1	1	1	1	1	1	Parts of line

**Load chart –LJ(Aux. hook) 12/12**

Load chart –LJ(Aux. hook) 12/12														
Boom 58m, Boom angle 65°														
Jib length (m) Radius (m)	22	25	28	31	34	37	40	43	46	49	52	55	58	Jib length (m) Radius (m)
40	11.6													40
44	10.3	10.1	9.9											44
48		9.0	8.7	8.4	8.2									48
52			7.8	7.5	7.3	7.1	6.8	6.6						52
56				6.7	6.5	6.3	6.0	5.8	5.6	5.3				56
60						5.6	5.3	5.2	5.0	4.7	4.5	4.2		60
64							4.7	4.6	4.4	4.1	3.9	3.7	3.4	64
68								4.0	3.9	3.6	3.4	3.2	2.9	68
72										3.1	3.0	2.8	2.5	72
76											2.5	2.4	2.1	76
Counter weight(t)	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	74+25	Counter weight(t)
Parts of line	1	1	1	1	1	1	1	1	1	1	1	1	1	Parts of line





## Zhejiang Sany Equipment Co.,LTD

SANY Crawler Crane Industrial Park, No. 2188 Daishan Road, Wuxing District, Huzhou City,  
Zhejiang Province, P. R. China Zip 313028  
Consulting [sanycrane@sanygroup.com](mailto:sanycrane@sanygroup.com) (Crane BU) / [crd@sany.com.cn](mailto:crd@sany.com.cn) (IHQ)  
After-sales Service 0086-400 6098 318

**Reminder:**

Any change in the technical parameters and configuration due to product modification or upgrade may occur without prior notice.  
The machine in the picture may include additional equipment. This brochure is for reference only, and goods in kind shall prevail.  
Copyright at SANY. No part of this brochure may be copied or used for any purpose without written approval from SANY.

© Edited in August 2024

